

PURCHASER	P.O. #	DATE
PROJECT	LOCATION	
ENGINEER	ARCHITECT	
SUBMITTED BY	FOR APPROVAL	FOR REFERENCE

ITEM	PLAN DESIGNATION	QUANTITY	COOLING BTU/H	VOLTAGE	FRIEDRICH MODEL

### Control Features

- Built-in Wi-Fi control on the go with the FriedrichGo™ App
- Smart home / voice command device compatibility (Amazon Alexa and Google Home)
- 24-hour timer
- Remote Control

### QuietMaster® Technology

- Heavy duty insulation on inner wall for sound absorption
- Stiffened sheet metal casing to block external noise
- Wide air discharge vents optimize airflow and minimize front panel noise
- Counterweights dampen vibration and decrease sound

### Comfort & Convenience

- 3 cooling and fan-only speeds, plus auto fan
- Unique sleep setting
- Auto restart saves settings if power is interrupted
- 8-way air flow control
- Washable, antimicrobial air filter

### Installation Features

- Slide-out chassis for easy removal for maintenance and service
- Includes standard installation hardware
- Expandable side curtains

### Earth Friendly

- ENERGY STAR® qualified models
- Money Saver® setting saves money by operating the fan only when cooling



QuietMaster®  
technology



Control  
with App



Save big  
on energy



Voice command  
compatible

# SPECIFICATIONS

★ ENERGY STAR® models



Model	UPC	Cooling Btu	Heating Btu	Volts Rated	Cooling Amps	Cooling Watts	EER	CEER	Estimated Yearly Energy Cost	Moisture Removal-Pints/HR	Refrigerant	CFM	Wt. Net/Ship Lbs.
<b>SLIDE OUT CHASSIS, COOL ONLY</b>													
★ CCW06B10B	724587440249	6000	—	115	4.3	492	12.1	12.1	\$54	0.9	R410A	200	44/51
★ CCW08B10B	724587440256	8000	—	115	5.8	661	12.0	12.0	\$69	1.0	R410A	250	44/61
★ CCW10B10A	724587439472	10000	—	115	7.3	826	12.1	12.0	\$95	1.2	R410A	300	51/68
★ CCW12B10A	724587439489	12000	—	115	8.6	992	12.0	12.0	\$107	1.5	R410A	330	64/86
★ CCW15B10A	724587439496	15000	—	115	11.0	1270	11.8	11.8	\$125	2.0	R410A	400	73/93
★ CCW18B30A	724587439502	18000	—	230	7.1	1525	11.8	11.8	\$149	2.7	R410A	520	106/136
★ CCW24B30A	724587439519	24000	—	230	10.2	2308	10.3	10.3	\$227	2.7	R410A	590	117/144
<b>SLIDE OUT CHASSIS, HEAT &amp; COOL</b>													
CEW08B11A	724587439526	8000	4200	115	6.3	670	11.0	11.0	\$61	2.1	R410A	250	44/61
CEW12B33A	724587439533	12000	10600	230	4.8	1060	11.0	10.9	\$96	3.3	R410A	265	64/86
CEW18B33A	724587439540	18000	10600	230	7.2	1600	11.0	11.0	\$159	5.5	R410A	430	106/136
CEW24B33A	724587439557	24000	10600	230	10.6	2340	10.1	10.1	\$222	6.5	R410A	560	117/144

# INSTALLATION

Model	Height Inches	Width Inches	Depth Inches	Depth From Front to Louvers	WINDOW INSTALLATION		THRU-WALL INSTALLATION		Carton Dimensions Inches		
					Window Width Inches	Minimum*	Maximum	Thru-the-wall Finished Hole Inches	Height	Width	Height
CCW06B10B, CCW08B10B	13 3/8	18 5/8	17 5/8	TBD	26	36	16	20	17	22	26
CEW08B11A, CCW10B10A, CCW12B10A, CEW12B33A,	14 5/8	19 3/4	23 3/4	9 1/2							
CCW15B10A, CCW18B30A, CEW18B33A	18	23 7/8	25 3/8	8 1/5	28	41	19	24	19 3/8	25 5/8	29 5/8
CCW24B30A, CEW24B33A	18 5/8	27	26 5/8	10 3/5	30	41	20	27 1/4	19 1/2	29 1/4	31

\* Minimum widths achieved using one side curtain assembly as opposed to both in a standard installation.

# CIRCUIT RATING/BREAKER/POWER CORD

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Power Cord Length (ft.)	Wall Outlet Appearance
CCW06B10B, CCW08B10B, CCW10B10A, CCW12B10A, CEW08B11A	125V - 15A	5-15P	6	
CCW15B10A			5.5	
CCW18B30A, CCW24B30A	250V - 20A	6-20P	4	
CEW12B33A, CEW18B33A, CEW24B33A			6	

As an ENERGY STAR® partner, Friedrich Air Conditioning Co. has determined that the selected ENERGY STAR® models meet the ENERGY STAR® guidelines for energy efficiency. EER is the unit's Energy Efficiency Ratio; CEER is the unit's Combined Energy Efficiency Ratio.

Your energy costs will depend on your utility rates and use. The estimated energy cost is based on an electricity cost of \$.12 per kWh. For more information, visit [www.ftc.gov/energy](http://www.ftc.gov/energy).

Due to continuing research in new energy-saving technology, specifications are subject to change without notice.

