




clé BASICS CARRARA

USAGE	Y/N
interior floor & wall	Y
exterior floor & wall	Y *
residential low traffic	Y
residential high traffic	Y
commercial low traffic	Y
commercial high traffic	N
radiant heating compatible	Y
fireplace surround	Y
shower	Y
steam shower (resealing yearly)	N
fountain	N
freeze thaw	N
pool	N
heat resistant	Y **
backsplash	Y
grout type	flexcolor cq
grout joint size	1/8"
UV resistant	Y



Standard thickness for carrara is 3/8". Please note all dimensions are nominal and can vary plus or minus 1/4".

* Exterior walls require vertical weather flashing and waterproof, penetrating sealant. Exterior floors must be installed above grade with waterproof, penetrating sealant.

** Carrara cannot withstand being exposed directly to fire but can withstand high heat and temperatures.

clé BASICS CARRARA INSTALLATION

What's in our tile: Honed white marble with delicate gray veining formed from the historic carrara stone quarried from the majestic mountains of Carrara, Italy. Our clé basics carrara collection is a classic white stone with a mixed fleuri and vein cut that blends to create subtle yet distinctive patterns.

clé has worked with our studios to provide the finest quality natural stone tiles available. However, for the best installation, it is important that you hire the highest qualified and experienced natural stone tile contractor for your project.

YOUR TILE INSTALLATION IS ONLY AS GOOD AS YOUR INSTALLER.

INSPECTING YOUR SHIPMENT

- With the clé basics carrara collection you will find a smooth honed surface with delicate gray veining.
 - **IMPORTANT:** Carrara will exhibit degrees of variation in color and shade. As our tiles are cut from large blocks of carrara, there is also variation between batches that will be hard to match with an add on order, please keep this in mind when calculating your order, and be sure to purchase enough material.
 - Industry standard suggests adding at least 15% overage due to tile cuts, potential breakage, or future repairs.
 - Dust and residue from shipping should be cleaned prior to installing. This can be done by simply wiping the back of each tile lightly with a damp sponge or soft cloth.
-

FOR INSTALLATION GUIDELINES

- clé's guides are only to help direct you in the right path for a proper installation. Each project is unique and therefore requires a professional natural stone installer who can provide the exact specifications for your project.
- Please refer to the current edition of the TCNA Handbook for detailed natural stone installation methods for your project's needs.
- Tile is merely the surface of your construction. Installation problems will arise from substrate or construction engineering and/or installation issues. Please refer to your project architect, structural engineer and/or installer to have the best results for your tile finish.
- As is standard in the tile industry, installation deems acceptance of materials. Do not install if there are visible issues. If you have any doubts or are unsure of what qualifies as a visible issue for the tile you are installing, please reach out to us prior to installation. Our tiles are subject to variations in color, texture, size and finish. Do not install if you have any doubts about visible issues. Misuse by contractor or end-user including but not limited to negligence, physical and/or chemical abuse is not covered by clé's warranty.
- **IMPORTANT:** Before installing, make sure to lay out your tile and blend so that variations in color and veining are where you would like them to be and are evenly distributed throughout the installation. Do not install without blending tiles from all boxes.
- Trim is unnecessary for carrara tiles. They merely need to be finished along the exposed edge by honing it to match the surface of the marble.

- Please note all carrara contains naturally occurring iron deposits that can cause rust spots activated by trapped moisture.
 - Do not soak carrara tiles or subject them to excessive moisture prior to installation and setting as this can cause iron spotting to occur.
 - Additionally, do not seal tiles if there is any excess moisture as this will trap moisture in the tile and create new staining probabilities.
- **IMPORTANT:** Carrara tiles are not freeze thaw rated. Therefore we do not recommend and cannot warrant installing these outdoors in areas that regularly experience freezing temperatures*

* If you plan on installing these outdoors in areas that experience freeze/thaw, we cannot guarantee there won't be installation failures. Installations in freeze/thaw locations require flashing the top of vertical installations to prevent moisture from dripping behind the installation and installing the tiles above grade for horizontal installations. In addition, the installation must be completely sealed and maintained with a waterproof sealant like Miracle 511 Porous Plus.

With application of Miracle Sealant, these tiles can have resistance to freeze/thaw issues. However, oftentimes there are installation failures because the specific installation guidelines and sealant maintenance is not properly followed. But if completed and maintained correctly (see manufacturer's instructions) then you can proceed WITH CAUTION.

If you can comply with all of the above and understand that without the sealant your install won't hold up—then it's up to you to proceed with installing this tile in a freeze/thaw location. We recommend your contractor reach out to both Mapei tech support for installation support and Miracle Sealant tech support on the waterproofing of the tiles.

GROUT GUIDELINES

- clé ONLY recommends [Mapei Flexcolor CQ](#) grout for carrara installations.
- Use of any other grout types can result in installation issues.
- For natural stone, a wide grout joint is not recommended as it will disrupt the variation and flow of tile color, veining and patterns.
- clé recommends a 1/8" grout joint.
- Penny rounds, 1" hexagon mosaics and 1"x3 3/4" herringbone mosaics come mounted on mesh sheets and will have a fixed 1/16" grout joint. 5" hexes come mounted on mesh sheets and will have a fixed 1/8" grout joint.
- Grout color selection is always up to our client and/or their design professional. However, clé is often asked for our opinion on best grout selections for our tiles. And due to the large array of grout colors that are now available, clé would like to offer this general guideline on a foolproof grout color selection for any of your clé tiles.
 - First, have your professional tile contractor complete your tile installation, except for the grout portion.
 - Next, when ready to grout, ask your contractor to bring ALL grout color charts from his preferred grout manufacturers, for your review.
 - Lastly, choose a time of day when you are most pleased with the lighting in your space (either natural lighting, installed lighting or a blend of both). During that lighting and time of day, select the grout color that best matches your tile selection.
- Note that the full Mapei Flexcolor CQ color catalogue contains 40 colors to choose from. Visit the [Mapei website](#) to view.

- If your contractor selects brands other than Mapei grout or Miracle sealant, please have them reach out to the respected representatives of those manufactures for advice and support on failures.
- **IMPORTANT:** During grout application, immediately remove any excess grout off the face of the tile with a clean, damp cloth/sponge to avoid grout haze.
- Any grout haze left by Mapei Flexcolor CQ can be removed with Mapei Ultracare Heavy-Duty Stone, Tile & Grout Cleaner.
- If your contractor is having any issues or questions regarding this grout, please reach out to Mapei tech support directly at 1-800-992-6273 as they are the best and fastest line of resolution.

MAINTENANCE &
SEALING GUIDELINES

- clé only recommends the use of Miracle 511 Porous Plus for an invisible sealant finish.
 - Like most natural stone, carrara requires sealing (before & after grouting) to prevent staining and help with repelling water.
 - Please consult with your natural stone installer on what sealing methods are best for your installation.
 - Applying sealant or using a grout release prior to grouting will minimize the risk of grout haze and will allow for easy clean up.
 - We recommended sealing the grout lines and tile surface in all applications of carrara (dry and wet) as the final step of installation.
 - Sealing floors further protects the tiles in moderate traffic areas.
 - Always test sealers in a small area to ensure it provides the finish you prefer.
 - For applications in wet areas, specific waterproofing precautions need to be taken such as using a waterproof membrane under the tile and use of Miracle 511 Porous Plus.
 - Single coat reapplication of the penetrating sealant is required once a year in shower applications due to the continuous exposure to water.
 - For superior water repellency in showers, we recommend applying Miracle 511 Impregnator in addition to Miracle 511 Porous Plus.
 - For showers, opening windows/doors to help some of the moisture dissipate faster after use will help rid extra moisture.
 - If your contractor is having any issues or questions regarding this sealant, please have them reach out to Miracle tech support directly at 1-877-385-8155 as they are the best and fastest line of resolution.
 - PLEASE FOLLOW ALL MIRACLE SEALANT INSTRUCTIONS FOR BEST RESULTS as well as MAINTENANCE UPKEEP RECOMMENDATIONS.*
- * **HINT:** if water or oil does not bead up on the surface of your tiles then the sealant was not applied properly.

CLEANING
GUIDELINES

- Carrara is chemically sensitive so only mild pH neutral cleaners should be used.
- As with any stone product, clé discourages the use of any surface cleansers or scrubbing pads. Cleaning stone requires only mild soap, water and soft cloths.
- Soapless cleaners are preferred because they minimize streaks and film.
- Mild, phosphate-free, biodegradable liquid dishwashing soaps or powders or stone soaps are acceptable if rinsing is thorough.
- Always avoid harsh chemicals and acidic or alkaline cleaning products.
- Showers and baths: soap scum can be minimized by using a squeegee after each use and using liquid as opposed to bar soaps.
- clé recommends the use of Miracle Porcelain & Ceramic Tile Cleaner to remove stubborn stains, grease build up, soap scum, hard water deposits and everyday grime.
- Miracle Tile & Stone Cleaner is effective as an ongoing maintenance cleaner and is gentle for everyday use.
- Vacuum or sweep regularly—abrasive dirt and materials can scratch the surface.
- Non-slip mats or area rugs should be placed inside and outside entrance ways to remove abrasive materials that can scratch and dirty the tile surface. Sand, dirt, and grit do the most damage to natural stone surfaces due to their abrasiveness.
- Dust mop interior floors frequently using a clean, non-treated dry dust mop.
- Interior wall installations can be cleaned with warm water and damp microfiber cloth.
- Grout lines can be cleaned with warm water and a nonmetal bristled cleaning brush.