




FORAGE TERRAZZO

USAGE	Y / N
interior floor & wall	Y
exterior floor & wall	N
residential low traffic	Y
residential high traffic	Y
commercial low traffic	Y
commercial high traffic	Y
industrial traffic	Y
radiant heating compatible	Y
fireplace surround	Y
shower	Y
steam shower (resealing yearly)	Y*
fountain	N
freeze thaw	N
pool	N
heat resistant	N
backsplash	Y
grout type	flexcolor cq
grout joint size	1/16"
UV resistant	Y



Standard thickness for 12"x24" and 24"x24" is 5/8" and 1/2" for 12"x12".

Please note all dimensions are nominal and can vary plus or minus 1/8".

* Not all steam shower companies can accommodate stone surfaces so be sure to check with your plumber for an appropriate steam shower supplier.



FORAGE TERRAZZO INSTALLATION

What's in our tile: Crafted in America, our polished terrazzo tile is made from tumbled stone in a cement base. These materials lend our forage collection natural, neutral shades that offer the quiet versatility of solid-color tile with the visual interest of a pattern. Perfectly at home in a mid-century setting, surrounded by wood paneling and an earthy palette, it also complements the classic glamor of marble and plaster or the clean serenity of ultramodern design.

clé has worked with our studios to provide the finest quality terrazzo tiles available.

However, for the best installation, it is important that you hire the highest qualified and experienced natural stone tile contractor for your project.

YOUR TILE INSTALLATION IS ONLY AS GOOD AS YOUR INSTALLER.

INSPECTING YOUR SHIPMENT

- With the Forage Terrazzo collection you will find a polished surface with slight beveled edges and extreme color variation derived from natural aggregate set in a cement base.
 - **IMPORTANT:** Due to the extreme color and shade variations, it is very important to blend the tiles from all boxes once they arrive and place them in their installation area to ensure you have the layout you want before installing.
 - Industry standard suggests adding at least 15% overage due to tile cuts, potential breakage, or future repairs.
 - Dust and residue from shipping should be cleaned prior to installing.
 - **NOTE:** Forage Terrazzo pieces come packed face to face and back to back with an application of wax strips applied to one face of each of the face to face tiles. The wax strips can easily be removed with a plastic putty knife or similar.
-

FOR INSTALLATION GUIDELINES

- clé's guides are only to help direct you in the right path for a proper installation. Each project is unique and therefore requires a professional natural stone installer who can provide the exact specifications for your project.
- Please refer to the current edition of the TCNA Handbook for detailed natural stone installation methods for your project's needs.
- Tile is merely the surface of your construction. Installation problems will arise from substrate or construction engineering and/or installation issues. Please refer to your project architect, structural engineer and/or installer to have the best results for your tile finish.
- As is standard in the tile industry, installation deems acceptance of materials. Do not install if there are visible issues. If you have any doubts or are unsure of what qualifies as a visible issue for the tile you are installing, please reach out to us prior to installation. Our tiles are subject to variations in color, texture, size and finish. Do not install if you have any doubts about visible issues. Misuse by contractor or end-user including but not limited to negligence, physical and/or chemical abuse is not covered by clé's warranty.
- **IMPORTANT:** Before installing, make sure to lay out your tile and blend so that variations in color are where you would like them to be and are evenly distributed throughout the installation. Do not install without blending tiles from all boxes.
- To ensure proper bonding when setting, we recommend lightly wiping the back of each tile if there is excessive dust.

- As with natural stone, we do not offer trim for our Forage Terrazzo. However, they can simply be finished by an installer to match the polished surface of the tiles or finished to create most forms of edge finishes—bullnose etc.
- For cutting or potentially mitering terrazzo, we recommend your installer use a wet saw with a diamond blade.
- To increase slip resistance on shower floors, tiles can be "scored" with a tile blade in desired increments to create grooves or cut down to 4" x 4" (or smaller) squares. Please refer to a professional stone installer for this.
- Please note, when using a waterproofing membrane for wet applications of Forage Terrazzo, we recommend the use of a premium rapid setting mortar to ensure the best performance.
 - We recommend [Mapei Ultralite SI Quick](#) or [Mapei Ultraflex LFT Rapid](#).
- [Mapei Ultralite mortar](#) can be used for dry applications of Forage Terrazzo.

GROUT GUIDELINES

- clé ONLY recommends Mapei Flexcolor CQ grout for Forage Terrazzo installations.
- Use of any other grout types can result in installation issues.
- Forage Terrazzo has an initial protectant—3M Scotchgard Stone Floor Protector that is applied on the terrazzo, therefore applying additional sealant or a grout release prior to grouting isn't required when using Flexcolor CQ grout.
- However If you choose to use a grout other than Flexcolor CQ, especially a highly pigmented grout, it is recommended to use a grout release prior to grouting. A test area is recommended to ensure the grout release was adequately applied.
- clé recommends a $\frac{1}{16}$ " grout joint.
- Grout color selection is always up to our client and/or their design professional. However, clé is often asked for our opinion on best grout selections for our tiles. And due to the large array of grout colors that are now available, clé would like to offer this general guideline on a foolproof grout color selection for any of your clé tiles.
 - First, have your professional tile contractor complete your tile installation, except for the grout portion.
 - Next, when ready to grout, ask your contractor to bring ALL grout color charts from his preferred grout manufacturers, for your review.
 - Lastly, choose a time of day when you are most pleased with the lighting in your space (either natural lighting, installed lighting or a blend of both). During that lighting and time of day, select the grout color that best matches your tile selection.
- Note that the full Mapei Flexcolor CQ color catalogue contains 40 colors to choose from. Visit the Mapei website to view.
- If you are working with a highly color-variegated tile or a combination of tiles (checkered or otherwise), we recommend that you follow the above recommendations—but match your grout to the color in your varied tile or tile combination that you would most like to accentuate.
- If your contractor selects brands other than Mapei grout, 3M or Miracle sealant, please have them reach out to the respected representatives of those manufactures for advice and support on failures.
- **IMPORTANT:** During grout application, immediately remove any excess grout off the face of the tile with a clean, damp cloth/sponge to avoid grout haze.
- If a slight grout haze occurs, it can be effectively removed from the tile by using a 3MTM Eraser Pad 3600 Pink pad with water and/or 3MTM Neutral Cleaner.
- If your contractor has any issues or questions, please reach out to Mapei tech support directly at 1-800-992-6273 for grout and 3M tech support directly at 1-800-626-8578 for 3M products.

MAINTENANCE &
SEALING GUIDELINES

- Forage Terrazzo tiles are applied with an initial protectant—3M Scotchgard Stone Floor Protector; a high performance floor surface hardener and protective clear coat for porous stone surfaces. It is highly resistant to scuffs, black marks, stains, scratches and soil.
- Please note, the initial 3M protectant on each tile is water resistant but not waterproof, therefore we recommend application of a waterproof, penetrating sealer to further protect the tile and grout lines in wet areas.
- For wet area applications, clé ONLY recommends the use of Miracle 511 Porous Plus for an invisible sealant finish. Grout lines and the tile surface must be sealed as the final step of installation.
- For dry applications including floors, we recommend sealing the grout lines with Miracle 511 Porous Plus as the final step of installation. Sealing will further protect the grout lines against staining.
- Always test sealers in a small area to ensure it provides the finish you prefer.
- PLEASE FOLLOW ALL MIRACLE SEALANT INSTRUCTIONS FOR BEST RESULTS as well as MAINTENANCE UPKEEP RECOMMENDATIONS.*

* **HINT:** if water or oil does not bead up on the grout lines then the sealant was not applied properly.

- Over time, a natural patina will occur on floors as they are maintained and naturally wear.
- No stripping is required to repair or recoat floors with 3M Scotchgard Stone Floor Protector.
- Flooring may be periodically burnished using a Scotch-Brite Purple Diamond Floor Pad Plus to maintain gloss. No additional Scotchgard Stone Floor Protector needs to be applied to restore gloss. A suggested burnishing schedule is:
 - Medium traffic areas: 3-4 times per month
 - Low traffic residential areas: 1-2 times per month
- Scotchgard Stone Floor Protector will wear down over time due to foot traffic. When traffic areas are no longer returned to gloss by burnishing, then reapplication of Scotchgard Stone Floor Protector should be applied.
 - Light to moderate traffic floors should be recoated at least once a year or as needed.
- Please reference the separate Scotchgard Stone Floor Protector maintenance guide and follow their procedures for reapplication.
- If scratches occur on the surface, the surface can be repaired by burnishing with Scotch-Brite Purple Diamond Floor Pad Plus and then a 3M Tan Burnish Pad 3400.
- Single coat reapplication of the penetrating sealant (Miracle 511 Porous Plus) is required once a year on grout lines and the tile surface in shower applications due to the continuous exposure to water.
- For showers, opening windows/doors to help some of the moisture dissipate faster after use will help rid extra moisture.
- If your contractor is having any issues or questions regarding these sealants, please have them reach out to Miracle tech support directly at 1-877-385-8155 and 3M tech support directly at 1-800-626-8578 as they are the best and fastest line of resolution.

CLEANING
GUIDELINES

- Always avoid harsh chemicals and acidic or alkaline cleaning products.
- Do not use spray buff products or chemical dust mop treatments.
- Clean up spills immediately and use a damp mop to mop lightly soiled floors with a neutral cleaner like 3M Neutral Cleaner.
- Dust mop, vacuum or sweep regularly to remove sand, dust and other contaminants off the surface. Abrasive dirt and materials can scratch the surface.
- Non-slip mats or area rugs should be placed inside and outside entrance ways to remove abrasive materials that can scratch and dirty the tile surface. Sand, dirt, and grit do the most damage to stone surfaces due to their abrasiveness.
- To ensure proper slip resistance, flooring should be cleaned regularly to keep dust, sand, oils and other contaminants off the surface.
- For more aggressive cleaning use a mechanical buffer or auto scrubber along with a 3MTM Red Buffer Pad 5100 and Neutral Cleaner per the manufacturer's recommendations.
- For cleaning combined with light polishing, the Scotch-Brite Purple Diamond Pad Plus may be used on an auto scrubber.
- Showers and baths: soap scum can be minimized by using a squeegee after each use and using liquid as opposed to bar soaps.
- Interior wall installations can be cleaned with warm water and damp microfiber cloth.
- Grout lines can be cleaned with warm water and a nonmetal bristled cleaning brush.