



The new Onspot ADR Valve Box

www.onspot.com









The Onspot ADR Valve Box

The electrical parts of an Onspot system have gotten an ADR Freigabe. It is issued by the German TÜV authorities.

This document makes it possible to register vehicles, with Onspot, according to the ADR regulation.

The VdTÜV certificate certifies that Onspot ADR valve box meets the requirements for equipment to be installed in an exposed environment on an ADR vehicle.

Technically it means that the product meets the requirements for installation outside zones 0 and 1 on vehicles of type EX / II, EX / III, AT, FL and OX. Since before it is also certified according the UNECE R10 regulations.

Easy to order the ADR version

When you fill out the Onspot Configurator you will have the correct articles in a list. You can e-mail that list directly to yourself.

The ADR Freigabe you can download on the homepage of Onspot

Satisfaction is guaranteed

Onspot comes with a 2-year factory warranty. If you are not satisfied with the Onspot system, there is also a 6-month repurchase guarantee.



Just press the button

Automatic snow chains are engaged and disengaged just by pressing a button. You don't even have to leave the cab.

Easy to install

You get a complete Onspot kit delivered. Using your standard tools, it is easily mounted in a few hours.

Uncomplicated and well-tried

Ingeniously simple and reliable. With a sturdy design that withstands heavy wear, Onspot in installed in more than 150,000 vehicles.

Fits any vehicle

The customised brackets are available for most vehicle brands and models.

One solution - many benefits

- The traction similar to conventional snow chains – by pressing a button!
- Permanently installed always at hands when you need them
- Engage/disengage while driving up to 50 km/h
- · Works forward and in reverse
- Reduces braking distance
- Increased safety and comfort for the driver
- · Virtually maintenance-free
- Reduced risk of costly downtime when roads are icy

...YOU'LL MAKE IT IN TIME

Technical specification: • Operating speed: 2-50 km/h

- Activation speed: max 50 km/h
 Pressure requirement: 7-10 bar
- · Chains: 6, 12 or 18 chains and 6 chains spark resistant
- Power supply: 24 V or 12 V, 8 A fuse Weight: Approx. 40 kg (complete system)

Member of VBG Group

ONSPOT