

# Safety Data Sheet – Asphalt Pavement Mix

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

## Section 1 – Identification:

**GHS product identifier:** Asphalt Pavement Mix  
**Chemical Name:** Mixture  
**CAS No.** Mixture  
**Trade Names** Petroleum Asphalt / Road Paving Asphalt / Hot Mix Asphalt / Blacktop / Bitumen Mix / Warm Mix Asphalt/ Asphalt Concrete  
**Recommended Use:** Road Paving Asphalt

**Supplier's Details:** CallananIndustries, Inc.  
 8 Southwoods Blvd. 4th Floor Albany, NY 12211  
 (518) 374-2222  
 www.callanan.com

**Emergency telephone number:** (518) 374-2222

## Section 2 – Hazards Identification:

**GHS Hazard Classification(s):** OSHA HCS (29 CFR 1910.1200) / GHS Classification - Not classified as dangerous for supply/use.

**Pictogram(s):**



**Signal Word:** Warning

**Hazard Statement(s):** Contact with hot ASPHALT PAVING MATERIALS can cause skin burns. May cause eye irritation.  
 Fumes may cause upper respiratory irritation (nose & throat). Skin contact may increase susceptibility to sunburn.  
 Poisonous hydrogen sulfide gas can accumulate in the head-space of containers of certain asphalt products.  
 Mechanical disruption (e.g., milling, cutting, chipping) of cured asphalt pavement may release crystalline silica dust from the aggregate.

**Precautionary Statement(s):** Avoid breathing dust/fume/gas/mist/vapors/spray.  
 As necessary, Wear protective gloves/protective clothing/eye protection/face protection.  
 Wash hands and exposed skin after use.

### Section 3 – Composition and Information on Ingredients:

**Substance and Mixture:** Asphalt Emulsion

Composition and Information on Ingredients	% wt.	CAS No.
Aggregate (crushed stone, sand, gravel, slag)	70 - 97	Various
Petroleum asphalt / bitumen <sup>^</sup>	3 - 7	8052-42-4
Reclaimed Asphalt Pavement (RAP)	0 - 25	Mixture
Reclaimed Asphalt Shingles (RAS)	0 - 10	Mixture
Polymers and Natural Rubbers	< 0.5	Various
Process oils (inherent in refined petroleum asphalt)	< 0.1	Various
Anti-strip or other amine-based additives	< 0.1	Various
Warm-mix additives	< 0.1	Various

<sup>^</sup>Contains: <0.05% of 3 - 7 ring Polycyclic Aromatic Hydrocarbons (PAHs).

Other Substances in the product which may present a health or environmental hazard, or which have been assigned occupational exposure limits, are detailed below. Please see Section 8 of SDS for more details.

- Contains: <0.1% airborne crystalline silica (inherent in aggregate) and <0.1% hydrogen sulfide.
- Hydrogen sulfide gas can accumulate in the head space of containers of certain asphalt products.
- Heated product releases asphalt fume.

Additional Information - None

### Section 4 – First Aid Measures:

#### Description of Necessary First Aid Measures:

<b>Eye Contact</b>	Flush eyes with water for at least 15 minutes while holding eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation develops and persists, get medical attention.
<b>Inhalation</b>	Not normally required. Move person to fresh air. Apply artificial respiration if necessary. If symptoms persist, obtain medical attention.
<b>Skin Contact</b>	Causes burns. Immediately cool skin where asphalt binder has adhered to skin. Allow asphalt binder which remains on the skin to fall off naturally. DO NOT REMOVE. If problem persist or coverage is extensive, get medical attention.
<b>Ingestion</b>	Not normally required. Do not induce vomiting. Do not give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

#### Most Important Symptoms and Effects, both Acute and Delayed:

None Known

#### Indication of any Immediate Medical Attention and Special Treatment:

None Known

### Section 5 – Firefighting Measures:

#### Extinguishing Media:

<b>Suitable extinguishing media</b>	Extinguish with carbon dioxide, dry chemical, foam or water spray.
<b>Unsuitable extinguishing media</b>	None anticipated.
<b>Special hazards arising from the substance or mixture</b>	Combustion causes toxic fumes. Combustion products: Carbon monoxide, Carbon dioxide, Nitrogen oxides, Sulfur oxides
<b>Advice for firefighters</b>	A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions.

## Section 6 – Accidental Release Measures:

### Personal Precautions, Protective Equipment and Emergency Procedures:

<b>General Measures</b>	Avoid contact with skin and eyes.
<b>Environmental Precautions</b>	Not normally required.
<b>Methods and Materials for Containment and Cleaning up</b>	Allow product to cool/solidify and pick up as a solid.
<b>Reference to Other Sections</b>	None
<b>Additional Information</b>	None

## Section 7 – Handling and Storage:

<b>Precautions for safe handling</b>	Avoid contact with skin and eyes.
<b>Conditions for safe storage, including incompatibilities</b>	<b>Storage Temperature:</b> Store at temperatures not exceeding the product's flash point. <b>Incompatible Materials:</b> Strong oxidizing agents.

## Section 8 – Exposure Controls Personal Protections:

### Product Information:

Substance	CAS Number	PEL (OSHA)* - (8hr TWA)	TLV (ACGIH) – (8hr TWA)	PEL (OSHA) – (STEL)	TLV (ACGIH) – (STEL)	Note:
Asphalt fume	-----	-----	0.5 mg/m <sup>3</sup> (I)	-----	-----	See below
Crystalline Silica (respirable particulate)	-----	$\frac{10 \text{ mg/m}^3}{\% \text{SiO}_2 + 2}$	0.025 mg/m <sup>3</sup> ^	-----	-----	See below
Hydrogen sulfide	7783-06-4	-----	1 ppm	20 ppm ceiling	5 ppm	50 ppm peak
(I) Inhalable benzene-soluble fraction; ^Suspected Human Carcinogen; *Refer to OSHA 29 CFR 1910.1000 & 29 CFR 1926.55; 8hr TWA = 8 hour time-weighted average; STEL = Short Term Exposure Limit.						
<b>Recommended Monitoring Method</b>		NIOSH 5042 (Asphalt Fume), NIOSH 7500 (Crystalline Silica), Electrochemical sensor (hydrogen sulfide).				

### Exposure Controls:

<b>Appropriate Engineering Controls</b>	Use only outdoors or in a well-ventilated area.
<b>Eye and Face Protection</b>	The following to be used as necessary: Safety Glasses
<b>Skin Protection</b>	The following to be used as necessary: Leather or thick textile gloves
<b>Respiratory Protection</b>	In case of inadequate ventilation wear respiratory protection. Use NIOSH approved respiratory protection. Air-purifying respirator with combination organic vapor cartridge / particulate filter may be sufficient. Check with protective equipment manufacturer's data.
<b>Thermal Hazards</b>	Use gloves with insulation for thermal protection, when needed.
<b>Environmental Exposure Controls</b>	Do not discharge waste and/or cleaning water via public sewer system. Ensure waste is collected and contained.

## Section 9 – Physical and Chemical Properties:

### Information on Basic Physical and Chemical Properties:

Appearance	Solid
Color.	Dark brown / Black
Odor	Asphalt / Bitumen
Odor Threshold (ppm)	Not available.
pH (Value)	Not available.
Melting Point (°C) / Freezing Point (°C)	Not available.
Boiling point/boiling range (°C):	> 371 (>700 °F)
Flash Point (°C)	> 232 (> 450 °F)
Evaporation Rate	Not available.
Flammability (solid, gas)	Not applicable.
Explosive Limit Ranges	Not applicable.
Vapor pressure (Pascal)	Not determined.
Vapor Density (Air=1)	Not determined.
Density (g/ml)	2.2 - 2.7
Solubility (Water)	Negligible
Solubility (Other)	Not known
Partition Coefficient (n-Octanol/water)	Not available.
Auto Ignition Point (°C)	Not available.
Decomposition Temperature (°C)	Not available.
Kinematic Viscosity (cSt) @ 40°C	Not available
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Other information	Not available.

## Section 10 – Stability and Reactivity:

<b>Reactivity</b>	Stable under normal conditions.
<b>Chemical Stability</b>	Stable
<b>Possibility of hazardous reactions</b>	May react violently with: Strong oxidizing agents
<b>Conditions to avoid</b>	Incompatible materials
<b>Incompatible materials</b>	Oxidizers
<b>Hazardous decomposition products</b>	Combustion causes toxic fumes. Combustion products: Carbon monoxide, Carbon dioxide, Nitrogen oxides, Sulfur oxides

## Section 11 – Toxicological Information:

**Exposure Routes:** Inhalation, Skin Contact, Eye Contact

### Information on Toxicological Effects:

<b>Acute Toxicity</b>	LD50 (rat): >5000 mg/kg bw LD50 (dermal): >2000 mg/kg bw LC50 (inhalation, fume): >94.4 mg/m <sup>3</sup>
<b>Irritation and Corrosively</b>	May cause irritation to skin, eyes and respiratory system.
<b>Sensitization</b>	Not to be expected
<b>Repeated Dose Toxicity</b>	NOAEL(rat): 28 mg/m <sup>3</sup> LOAEL (rat): 149 mg/m <sup>3</sup>
<b>Carcinogenicity</b>	Not to be expected at typical road paving temperatures

<b>NTP</b>	<b>IARC</b>	<b>ACGIH</b>	<b>OSHA</b>
No.	2B*	No.	No.

<b>Mutagenicity</b>	Not to be expected
<b>Reproductive Toxicity</b>	Not to be expected
<b>Other Information</b>	* IARC (2013, volume 103) identifies that “occupational exposures to straight-run bitumens and their emissions during road paving are possibly carcinogenic to humans (Group 2B).” However, classification as a carcinogen under OSHA 29 CFR 1910.1200 is not warranted given the absence of positive cancer findings in human epidemiological studies and in cancer studies with laboratory animals when exposed dermally or by inhalation to asphalt products or fume condensates that are typical of road paving applications. IARC (2013, volume 103) also identifies that “occupational exposures to oxidized bitumens and their emissions during roofing are probably carcinogenic to humans (Group 2A).” Roofing shingle are sometimes recycled into road paving asphalt mix. Emissions from oxidized bitumen, e.g., from shingles, at road paving temperatures are not expected to be qualitatively different than emissions from straight-run bitumens, and therefore would not warrant a carcinogen classification under OSHA 29 CFR 1910.1200.

## Section 12 – Ecological Information:

### Eco-toxicity:

<b>Short Term</b>	LL50 (48 hour): >1000 mg/l (Fish) LL50 (48 hour): >1000 mg/L (Aquatic Invertebrates) EL50 (48 hour): >1000 mg/L (Aquatic Plants)
<b>Long Term</b>	No data

<b>Persistence and Degradability</b>	The product is poorly biodegradable.
<b>Bio-accumulative Potential</b>	The product has low potential for bioaccumulation.
<b>Mobility in Soil</b>	The product has low mobility in soil.
<b>Results of PBT and vPvB Assessment</b>	Not classified as PBT or vPvB.
<b>Other Adverse Effects</b>	None Known

## Section 13 – Disposal Considerations:

<b>Waste Treatment Methods</b>	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
<b>Additional Information</b>	None Known

## Section 14 – Transportation Information:

Ground or Water Domestic Voyage (DOT)	Not regulated when transported below 240°C (464 °F).
---------------------------------------	--

## Section 15 – Regulatory Information:

### Safety, Health and Environmental Regulations and Legislation Specific for the Substance or Mixture:

TSCA (Toxic Substance Control Act)	Inventory Status: All components listed or polymer exempt.
RCRA Hazardous Waste Number (40 CFR 261.33)	None
US RCRA Hazard Class	Not Applicable

### Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Chemical Name	CAS No.	Typical % wt.	RQ (Pounds)
None	-----	-----	-----

SARA 311/312 – Hazard Categories: None

### SARA 313 – Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical % wt.
None	-----	-----

### SARA 302 – Extremely Hazardous Substances (40 CFR 355):

Chemical Name	CAS No.	Typical % wt.	TPQ (Pounds)
None	-----	-----	-----

## Section 16 – Other Information:

Date of Issue: 04/28/2015

Last Revised: 05/11/2018

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*