

Date: 12/26/2021

Count | Description

NBS 040-135/11.81



Product photo could vary from the actual product

Product No.: 92559811

The pumps are non-self-priming, single-stage, centrifugal volute pumps with axial inlet port, radial outlet port and horizontal shaft.

The pump has a back pull-out design enabling removal of the motor, motor stool, cover and impeller without disturbing the pump housing or pipework.

All pumps are according to ISO 5199 standards, adjusted for American dimensions on pump and its flanges.

Inlet and outlet flanges are according to ASME 16.1/16.42. Dimensions and rated performance are according to 175/363 PSI (12/25 bar).


The mechanical shaft seal has dimensions according to EN 12756.

Motors are with main dimensions to NEMA standards. The pumps can be equipped with an MLE motor with integrated frequency converter or connected to a Grundfos CUE external frequency converter.



Date: 12/26/2021


92559811 NBS 040-135/11.81 AASG6S5ESBQQERX4 60 Hz





Date: 12/26/2021

Description	Walina	
Description General information:	Value	
	NBS 040-135/11.81	
Product name:	AASG6S5ESBQQERX4	
Product No.:	92559811	
EAN:	5715116261638	
Price:		
Technical:		
Rated pump speed:	1770 rpm	
Rated flow:	866 US gpm	
Rated head:	130.4 ft	
Actual impeller diameter:	11.8 in	
Code for shaft seal:	BQQE	
Curve tolerance:	2B HI 14.6:2016	
Pump version:	A	
Materials:		
Pump housing:	Cast iron	
Pump housing:	EN-GJL-250	
Pump housing:	ASTM A48-35	
Impeller:	Stainless steel	
Impeller:	EN 1.4308	
Impeller:	AISI 304	
Shaft:	Stainless steel	
Shaft:	EN 1.4462	
Shaft:	SAF 2205	
Internal pump house coating:	No coating	
Material code:	S5	
Code for rubber:	E	
Installation:	404.05	
t max amb:	104 °F	
Maximum operating pressure:	174.05 psi	
Type of connection: Size of inlet connection:	ANSI DN 125	
Size of inlet connection: Size of outlet connection:	DN 100	
Pressure rating for connection:	Class 125	
Mounting options design code:	В	
Support block (Yes/No):	Y	
Connect code:	G	
Liquid:		
Pumped liquid:	Water	
Liquid temperature range:	-13 248 °F	
Selected liquid temperature:	68 °F	
Density:	62.29 lb/ft³	
Electrical data:		
Motor standard:	NEMA	
IE efficiency class:	IE3 / NEMA Premium	
Rated power - P2:	40 HP	
Main frequency:	60 Hz	
Rated voltage:	3 x 230/460 V	
Rated current:	96-48 A	
Rated speed:	1770 rpm	
Number of poles:	4	
Enclosure class (IEC 34-5):	TEFC	
Mounting designation (IEC 34-7, Code I):	NEMA type C / foot	
Others:		
DOE Pump Energy Index CL:	0.94	
Net weight:	933 lb	
Gross weight:	935 lb	
Shipping volume:	19.6 ft³	






		Date:	12/26/2021	
Description	Value US			
Description Country of origin:	US			



12/26/2021 Date:

92559811 NBS 040-135/11.81 AASG6S5ESBQQERX4 60 Hz



Note! All units are in [in] unless otherwise stated. Disclaimer: This simplified dimensional drawing does not show all details.