## clare™



## ClareVision 8MP IP Bullet Camera, 2.8 mm Lens, Starvis, WDR, (White | Black)

CLR-V200-8B28W | CLR-V200-8B28B



Featuring the 8MP, Sony<sup>®</sup> Starvis<sup>™</sup> sensor, this Performance Series ClareVision Bullet camera includes a 2.8 mm lens with a maximum recording resolution of 3840 x 2160. Additionally, the camera includes support for True WDR, allowing you to adjust the image settings to compensate for brightness, exposure, and contrast. The camera can be used standalone when paired with a micro SD card up to 512 GB in size, or through an NVR.

## Performance Highlights:

- 8MP, 4K Sony<sup>®</sup> Starvis<sup>™</sup> capable of recording resolutions up to 3840 x 2160 at 20 FPS
- Supports micro SD card up to 512 GB for local storage
- Features built-in microphone
- IR night vision up to 25 meters
- IP67 rated ingress protection against weathering elements, dust, and debris
- ClareOne and Control4 driver support
- Features 3D DNR and True WDR
- Available in white and black color variations
- NDAA Compliant

SpecificationsCamera ParametersImage sensor4K, 8MP (3840 x 2160 @ 20 FPS)Sensor typeSony* Starvis**Lens28 mmAspect ratio16.9Minimum Illumination0.01 Lux, F1.6Field of view107* horizontalVideo ParametersStreamsMain stream: Up to max resolution H.265+, H.264, 30 FPS Sub stream: 720 x 480 @ 30 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264Frame rate3840 x 2160 @ 20 FPS 2560 x 1440 @ 30 FPS 1920 x 1080 @ 30 FPSMiror modeYesSnapshotYesIR range25 m 82 ft)Rato switchYesBacklight compensationYesMoto of parameters30 DNRAudio input/outputBuilt-In microphoneEventSmare vents (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersSupports up to 512 GBNetwork ParametersSupports up to 512 GBSto card includedNoBrowser supportChare, Control4PowerDC 12v, 700MA, POE (802.3af)ColorWhite, blackWeight16 (7257 g)Operating temperature-22* to 140° F (-30° to 60° C)Dimensions (W x H z0)29x 28x 6.7 in (73.66 x 71.12 x 170.18 mm)		
Inage sensor4K, 8MP (3840 x 2160 @ 20 FPS)Sensor typeSony* Starvis"Lens2.8 mmAspect ratio16:9Minimu illumination0.01 Lux, F1.6Field of view10" horizontalVideo ParametersVideo ParametersStreamsMain stream: Up to max resolution H.265+, H.265, H.264, 10 °PS °, Sub stream: 720 x 480 @ 30 FPS, H.265, H.264, 10 °PS °, 1200 x 1080 @ 30 FPS °, 1200 X 1000 @ 1000 Col	Specifications	
Sensor typeSony* Starvis™Lens2.8 mmAspect ratio16:9Minimum illumination0.01 Lux, F1.6Field of view10° horizontalVideo ParametersStreamsMain stream; Up to max resolution H.265+, H.265, H.264, 30 FPS Sub stream: 720 x 480 @ 30 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264Miror modeYesMiror modeYesRange25 m 82 ft)Rauto switchYesIR wavelength850 nmBacklight compensationYesNDRJD DNRAudio input/outputBult-In microphoneEventSuports up to f12 GBNotion detectionSorart events (line crossing, loitering, human body detection, intrusion, people gather)Alarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportClare, Control4PowerCla	Camera Parameters	
Lens2.8 mmAspect ratio16.9Minimum illumination0.01 Lux, F1.6Field of view107° horizontalVideo ParametersStreamsMain stream: Up to max resolution H.265+, H.265, H.264, JC44, 30 FPS Sub stream: 720 x 480 @ 30 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264Frame rate3840 x 2160 @ 20 FPS Sco x 1440 @ 30 FPS 1920 x 1080 @ 30 FPSMirror modeYesSnapshotYesIR ange25 m 82 ft)IR vavelength850 nmBacklight compensationYesWDRTrue WDRDNR30 DNRAudio input/outputBuilt-In microphoneEventYesMotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersSupports up to 512 GBAlarm input/outputNoLocal storageSupports up to 512 GBStorageClare, Control4PowerClare, Control4PowerClare, Control4PowerClare, Control4Power22° to 140° F (-30° to 60° C)Dimensions (W x H x D)29x 28 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Image sensor	4K, 8MP (3840 x 2160 @ 20 FPS)
Aspect ratio16.9Minimum illumination0.01 Lux, F1.6Field of view107° horizontalVictoe ParametersStreamsMain stream: Up to max resolution H.265+, H.265, H.264, Tertiary: 1280 x 720 ø 15 FPS, H.265, H.264Frame rate3840 x 2160 @ 20 FPS 2560 x 1440 @ 30 FPS 1290 x 1080 @ 30 FPSMirror modeYesRange25 m 82 ft)Ratus switchYesIR audo switchYesBacklight compensationYesVDRTrue WDRDNR30 DNRAudio input/outputBulti-In microphoneAudio input/outputSult-In microphoneForentYesNetworkPOE IEEE 802.3afAudio input/outputNoAudio input/outputNoAudin input/outputNoSubser supportGorentalAuser supportSupports up to 512 GBStorad includedNoStorad includedNo<	Sensor type	Sony® Starvis™
Minimum illuminationOut Lux, F1.6Field of view107° horizontalVideo ParametersStreamsMain stream: Up to max resolution H.265+, H.265, H.264, 30 FPS Sub stream: 720 x 480 @ 30 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264Frame rate3840 x 2160 @ 20 FPS 2560 x 1440 @ 30 FPS 1920 x 1080 @ 30 FPSMirror modeYesSnapshotYesRange25 m 82 ft)IR auto switchYesIR wavelength850 nmBacklight compensationYesVDRTrue WDRDNR3D DNRAudio input/outputBuilt-in microphoneEventYesMotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersYoe IEEE 802.3afAudio storageSupports up to 512 GBSol card includedNoIocal storageSupports up to 512 GBSol card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWite, blackWeather ratingP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)29 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Lens	2.8 mm
Field of view107° horizontalVideo ParametersWain stream: Up to max resolution H.265+, H.265, H.264, 30 FPS Sub stream: 720 x 480 @ 30 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264Frame rate3840 x 2160 @ 20 FPS 2560 x 1440 @ 30 FPS 1920 x 1080 @ 30 FPSMirror modeYesSnapshotYesIR range25 m 82 ft)IR auto switchYesBacklight compensationYesVDRTue WDRDNR3D DNRAudio input/outputBuilt-in microphoneEventVesNotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersVesNaturo input/outputNoAudio input/outputNoData iniput/outputNoStoreralCorrole (line crossing, loitering, human body detection, intrusion, people gather)PreventCorrole (line crossing, loitering, human body detection, intrusion, people gather)Audio input/outputNoNoSo corrole (line crossing, loitering, human body detection, intrusion, people gather)PreventCorrole (line crossing, loitering, human body detection, intrusion, people gather)Prevent <td< td=""><td>Aspect ratio</td><td>16:9</td></td<>	Aspect ratio	16:9
Video ParametersVideo ParametersStreamsMain stream: Up to max resolution H.265+, H.265, H.264, 30 FPS Sub stream: 720 x 480 @ 30 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264Frame rate2840 x 2160 @ 20 FPS 2560 x 1440 @ 30 FPS 1920 x 1080 @ 30 FPSMirror modeYesSnapshotYesIR range25 m 82 ft)IR auto switchYesIR auto switchYesBacklight compensationYesVDRTrue WDRDNR3D DNRAudio input/outputBuilt-in microphoneEventVesNotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersVole IEEE 802.3afGeneralNoSD card includedNoSo control4NoPowerC1arc, Control4PowerC1arc, Control4PowerC12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22* to 140° F (-30° to 60° C)Dimensions (W x H x D)29 x 28 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Minimum illumination	0.01 Lux, F1.6
StreamsMain stream: Up to max resolution H.265+, H.265, H.264, 30 FPS Sub stream: 720 x 480 @ 30 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264Frame rate& 840 x 2160 @ 20 FPS 2560 x 1440 @ 30 FPS 1920 x 1080 @ 30 FPSMirror modeYesSnapshotYesIR range25 m 82 ft)IR auto switchYesBacklight compensationYesWDRTrue WDRDNR3D DNRAudio input/outputBuilt-in microphoneEventNetwork ParametersNotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersVesNetwork ParametersSupports up to 512 GBAlarm input/outputNoIocal includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerClare, Control4PowerP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Field of view	107° horizontal
H264, 30 FPS Sub stream: 720 x 480 @ 30 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264 Tertiary: 1280 x 720 @ 15 FPS, H.265, H.264Frame rate3840 x 2160 @ 20 FPS S1920 x 1080 @ 30 FPSMirror modeYesMirror modeYesIR range25 m 82 ft)IR auto switchYesIR auto switchYesBacklight compensationYesVDRTrue WDRDNR3D DNRAudio input/outputBuilt-in microphoneEventSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersVesNetworkPOE IEEE 802.3afGeneralSuports up to 512 GBSlo card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Video Parameters	
Number2560 x 1440 @ 30 FPS 1920 x 1080 @ 30 FPSMirror modeYesSnapshotYesIR range25 m 82 ft)IR auto switchYesIR auto switchYesIR wavelength850 nmBacklight compensationYesWDRTrue WDRDNR3D DNRAudio input/outputBuilt-in microphoneEventSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersYoe IEEE 802.3afAurin input/outputNoLocal storageSuports up to 512 GBSD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerCl 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)29 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Streams	H.264, 30 FPS Sub stream: 720 x 480 @ 30 FPS, H.265, H.264
SnapshotYesIR range25 m 82 ft)IR auto switchYesIR wavelength850 nmBacklight compensationYesWDRTrue WDRDNR3D DNRAudio ParametersAudio input/outputBuilt-in microphoneEventVortex Signal events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersVortex Signal events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersVortex Signal events (line crossing, loitering, human body 	Frame rate	2560 x 1440 @ 30 FPS
IR range 25 m 82 ft)   IR auto switch Yes   IR auto switch 850 nm   Backlight compensation Yes   WDR True WDR   DNR 3D DNR   Audio Parameters 3D DNR   Audio input/output Built-in microphone   Event Smart events (line crossing, loitering, human body detection, intrusion, people gather)   Notion detection Smart events (line crossing, loitering, human body detection, intrusion, people gather)   Network Parameters VER   Network POE IEEE 802.3af   General Supports up to 512 GB   Alarm input/output No   Local storage Supports up to 512 GB   SD card included No   Privers Clare, Control4   Power DC 12V, 700MA, POE (802.3af)   Color White, black   Weather rating IP67   Operating temperature -22° to 140° F (-30° to 60° C)   Dimensions (W x H x D) 2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)	Mirror mode	Yes
IR auto switchYesIR wavelength850 nmBacklight compensationYesWDRTrue WDRDNR3D DNRAudio ParametersAudio input/outputBuilt-in microphoneEventMotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersNoNetwork ParametersSupports up to 512 GBAlarm input/outputNoLocal storageGupports up to 512 GBSD card includedNoBrowser supportClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Snapshot	Yes
IR wavelength850 nmBacklight compensationYesWDRTrue WDRDNR3D DNRAudio ParametersAudio input/outputBuilt-in microphoneEventMotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersVNetwork ParametersSole IEEE 802.3afAdam input/outputNoLocal storageSupports up to 512 GBSD card includedNoSol card includedChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackVeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 7.1.12 x 170.18 mm)Weight1.6 lb (725.74 g)	IR range	25 m 82 ft)
Backlight compensationYesBacklight compensationYesWDRTrue WDRDNR3D DNRAudio ParametersAudio input/outputBuilt-in microphoneEventMotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersVertwork ParametersNetwork ParametersPOE IEEE 802.3afGeneralSupports up to 512 GBAlarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	IR auto switch	Yes
WDRTrue WDRDNR3D DNRAudio ParametersAudio input/outputBuilt-in microphoneEventMotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersVNetwork ParametersVOE IEEE 802.3afGeneralSupports up to 512 GBAlarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	IR wavelength	850 nm
DNR3D DNRAudio ParametersAudio input/outputBuilt-in microphoneEventSmart events (line crossing, loitering, human body detection, intrusion, people gather)Motion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersPOE IEEE 802.3afMetminput/outputNoAlarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)29 x 2.8 x 6.7 in (73.66 x 7.1.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Backlight compensation	Yes
Audio ParametersAudio input/outputBuilt-in microphoneEventEventMotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersPOE IEEE 802.3afGeneralVoe IEEE 802.3afAlarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	WDR	True WDR
Audio input/outputBuilt-in microphoneEventMotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersVNetwork ParametersPOE IEEE 802.3afGeneralVAlarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackVeather ratingIP67Operating temperature2.2° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)	DNR	3D DNR
EventMotion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersNetworkPOE IEEE 802.3afGeneralAlarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature2.2° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Audio Parameters	
Notion detectionSmart events (line crossing, loitering, human body detection, intrusion, people gather)Network ParametersNetworkPOE IEEE 802.3afGeneralNoAlarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Audio input/output	Built-in microphone
Aeter at a generalNetwork ParametersNetworkPOE IEEE 802.3afGeneralAlarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Event	
NetworkPOE IEEE 802.3afGeneralAlarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Motion detection	
GeneralAlarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Network Parameters	
Alarm input/outputNoLocal storageSupports up to 512 GBSD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Network	POE IEEE 802.3af
Local storageSupports up to 512 GBSD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	General	
SD card includedNoBrowser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Alarm input/output	No
Browser supportChrome, EdgeDriversClare, Control4PowerDC 12V, 700MA, POE (802.3af)ColorWhite, blackWeather ratingIP67Operating temperature-22° to 140° F (-30° to 60° C)Dimensions (W x H x D)2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)Weight1.6 lb (725.74 g)	Local storage	Supports up to 512 GB
Drivers Clare, Control4   Power DC 12V, 700MA, POE (802.3af)   Color White, black   Weather rating IP67   Operating temperature -22° to 140° F (-30° to 60° C)   Dimensions (W x H x D) 2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)   Weight 1.6 lb (725.74 g)	SD card included	No
Power DC 12V, 700MA, POE (802.3af)   Color White, black   Weather rating IP67   Operating temperature -22° to 140° F (-30° to 60° C)   Dimensions (W x H x D) 2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)   Weight 1.6 lb (725.74 g)	Browser support	Chrome, Edge
Color White, black   Weather rating IP67   Operating temperature -22° to 140° F (-30° to 60° C)   Dimensions (W x H x D) 2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)   Weight 1.6 lb (725.74 g)	Drivers	Clare, Control4
Weather rating IP67   Operating temperature -22° to 140° F (-30° to 60° C)   Dimensions (W x H x D) 2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)   Weight 1.6 lb (725.74 g)	Power	DC 12V, 700MA, POE (802.3af)
Operating temperature -22° to 140° F (-30° to 60° C)   Dimensions (W x H x D) 2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)   Weight 1.6 lb (725.74 g)	Color	White, black
Dimensions (W x H x D) 2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)   Weight 1.6 lb (725.74 g)	Weather rating	IP67
Weight 1.6 lb (725.74 g)	Operating temperature	-22° to 140° F (-30° to 60° C)
· ·		2.9 x 2.8 x 6.7 in (73.66 x 71.12 x 170.18 mm)
Compliance	-	1.6 lb (725.74 g)
•	Compliance	

ETL/ETL-C, IC, CE, FCC, ROHS, ONVIF S/T

By making technology simple, Clare provides exclusive benefits to integrators, builders, and end users. We offer innovative smart home and business solutions, wireless security, controllable lighting, and IP CCTV components. For more information, visit www.clarecontrols.com.

Certifications