

Soft Gripper

Explore new automation possibilities with certified food-grade soft gripper



TECHNICAL SPECIFICATIONS

General Properties	Minimum	Typical	Maximum	Unit
Material	Two-component silicone rubber			
Food approval	FDA 21 CFR 177.2600 & EC/EU - 1935/2004			
Operation cycles	2.000.000			[cycles]
Operation temperature	-20 / -4		80 / 176	[C] / [F]
SG-tool attachment mechanism	Quick-lock and Smart-lock			
Weight Base Part	0.77 / 1.69			[kg] / [lb]
SG-a-H / SG-a-S				
Max payload	-	-	2.2 / 1.5 4.85 / 3.3	[kg] [lb]
Work range, Grip dimensions (A)	11 / 0.43	-	75 / 2.95	[mm] / [inch]
Work range, Grip depth (B)	-	38 / 1.496	-	[mm] / [inch]
Soft part (SG-a-S) (C)	-	16 / 0.63	-	[mm] / [inch]
Dimensions (HxØmax)	76x112 / 3 x 4.4			[mm] / [inch]
Weight (smart lock included)	0.168 / 0.37			[kg] / [lb]
SG-b-H				
Max payload	-	-	1.1 / 2.42	[kg] / [lb]
Work range, Grip dimensions (A)	24 / 0.94	-	118 / 4.65	[mm] / [inch]
Work range, Grip depth (B)	-	40 / 1.57	-	[mm] / [inch]
Dimensions (HxØmax)	77x109 / 3.03 x 4.29			[mm] / [inch]
Weight (smart lock included)	0.172 / 0.379			[kg] / [lb]

POWER UP PRODUCTION

- Explore new possibilities for food and beverage automation with certified food-grade soft gripper
- Easily handle a wide array of irregular shapes and delicate objects with flexible silicon-molded gripper
- Safely handle fragile and delicate objects for higher production quality and reduced waste
- No external air supply means no dust, no noise, no complexity, and no additional costs