

**BLAST CHILLER/SHOCK  
FREEZER REACH-IN,  
SELF-CONTAINED**

VBCF-12-100U

- 3 Year Parts & Labor Warranty Plus an Additional  
2 Year Compressor Warranty

- Exclusive 2 Year Warranty on Magnetic Door Gaskets

**VICTORY**  
**ULTRASPEC®**

### STANDARD FEATURES

- Soft and Hard, Timed or Core Probe Blast Chilling
- Soft and Hard, Timed or Core Probe Shock Freezing
- Automatic Recognition of Core Probe
- Multi Point Sensor Temperature Display Button
- USB Data Recorder
- Core Probe Heater Button
- HACCP Alarm Display Button
- Pre-Cooling Cycle Button
- Adjustable Evaporator Fan Speed Button
- Timed Manual Defrost Button
- Infinity Mode Program with Adjustable Set Point
- Automatic Conservation Mode at End of Cycle
- On Board Recipe Book with 68 Pre-Set Programs
- 99 Free Memory Positions for Custom Programs
- LCD Illuminated Temperature Display
- Real Time Clock
- RS 485 Connection
- One, High Precision Heated Multi Sensor Probe
- Adjustable Stainless Steel Feet



VBCF-12-100U

### OPTIONS & ACCESSORIES

- UV Sterilization Lamp
- Casters with Brakes
- Single Sensor Probes (up to 4 possible)
- Change Door Swing



## VBCF CABINET CONSTRUCTION

Stainless steel AISI 30418/10 exterior and interior. Die-formed interior floor has rounded corners and central drain for easy cleaning. High density foamed in place CFC and HCFC free expanded polyurethane insulation (3.15" thick). Anti-condensation perimeter heating around door opening. Non toxic epoxy coated evaporator coil. One, heated, high precision multi-sensor core probe and adjustable stainless steel legs are standard.

## VBCF DOOR CONSTRUCTION

Ergonomic vertical door handle and stainless steel AISI 304 18/10 construction. Snap in place magnetic gaskets Self closing doors with hold open stop at 100°.

## VBCF REFRIGERATION SYSTEM

The self-contained refrigeration system uses R404A refrigerant and features a hermetically sealed compressor with overload protection. An evaporator fitted with a high flow rate fan insures maximum cooling efficiency. Indirect air flow assures highest product quality. Manual defrosting with door open on a timed cycle.

## VBCF INTERIOR STORAGE ARRANGEMENTS

Stainless steel wire guide rack allows for maximum air circulation and can be easily removed without tools for cleaning. See specific model characteristics for pan capacity (number of pans and sizes). Pans not included. Spacing between pans is on 2.56" centers. Unit will hold 18" x 26" or 12" x 20" pans.

## VBCF ELECTRONIC CONTROL SYSTEM

Electronic control with LCD/color display insures precise control of Blast Chilling (194° F to 37° F in 90 Minutes) or Shock Freezing (194° F to 0° F in 240 Minutes) Cycles. One touch hard and soft auto-matic blast chilling or shock freezing cycles based either on core probe temperature or timed cycle. Automatic recognition of the core probe and automatic conservation mode at the end of a cycle. One touch display of HACCP Alarms (power failure, cycle time out of HACCP required time, high temp, low temp) recorded in memory. The real time clock provides date, time, and duration of HACCP alarms (power failure, cycle time out of HACCP required time, high temp, low temp) recorded in memory. Will record up to 10 alarm events before over writing the first alarm and will keep the data for a minimum of 48 hours in case of a power failure. On board program memory holds 99 total cycles (68 factory pre-set recipes, up to 31 custom programs). Adjustable Evaporator Fan Speed button allows for regulation of the fan during the blast chilling or shock freezing cycle. Compressor protected by overload cut-out with automatic reset. Micro-switch control cuts out the evaporator fan and compressor whenever the door is opened.

| CHARACTERISTICS                     | VBCF-12-100U |
|-------------------------------------|--------------|
| Width, Overall (in.)                | 33.5         |
| Depth, Overall (in.)                | 33.5         |
| Height, Overall (with legs, in.)    | 70.9         |
| Depth, Door Open 90°                | 65.4         |
| Clear Door Height (in.)             | 32.7         |
| Clear Door Width (in.)              | 28.7         |
| Internal Depth (in.)                | 20.1         |
| Wall Thickness (in.)                | 2.4          |
| Sheet Pan Capacity                  | 12           |
| Size of Pans                        | 18"x26"x1"   |
| Centers Between Pans (in.)          | 2.56         |
| Chilling Capacity in 90 min (lbs.)  | 100          |
| Freezing Capacity in 240 min (lbs.) | 70           |

| ELECTRICAL DATA |              |
|-----------------|--------------|
| Cabinet Voltage | 208-240/60/3 |
| NEMA Plus       | 15-20P       |
| Total Amperes   | 9.0          |
| Horse Power     | 2 3/4 HP     |

| REFRIGERATION DATA |       |
|--------------------|-------|
| Refrigerant        | R404A |
| BTUH               | 6195  |
| Climate Class      | T     |

| CRATED DIMENSIONS      |          |
|------------------------|----------|
| Crated H x W x D (in.) | 78x37x37 |
| Crated Weight (lbs.)   | 535      |
| Uncrated Weight (lbs.) | 436      |

VBCF Evap. Temp -10° F, Ambient Temp. 90° F

