### **Turret Series LED**

How You Round Out the Ultimate Line of Industrial LED Lighting



# WHEN YOU WANT TO GO ROUND, CALL IN THE BIG GUNS.

Round fixtures have their advantages. You don't have to worry about orientation. So, you can expedite installation. But don't sacrifice performance or longevity for convenience. With the Turret Series, you get that ideal combination of all three.



### Military-Grade for Added Reliability

What does Tactik Military-Grade look like? Try a heat rating of up to 203°F with no fall-off in lumen output as temperatures approach the rated limit.



### Keep Your Cool with a Remote Driver

Tactik features remote drivers to prevent unwanted heat build-up, extending fixture life. They also allow lighting layouts to be easily adjusted to plant floor updates – without costly re-gridding.



#### 5-7 Day Lead Time

Our innovative modular design and advanced manufacturing capabilities allow us to ship all orders, even customizations, in 5-7 days.





### **Turret Series LED**


**Round Made Right** 

### ENHANCE COOLING AND ELIMINATE RE-GRIDDING HEADACHES


With leading competitive units, the LED driver is inside the light, which results in a lot of heat. However, the Turret Series features remotely mounted drivers.

This approach helps keep the operating temperatures inside the fixture lower. It also allows more effective cooling of the driver, safeguarding the integrity of the driver as well as the LED light itself.

Should changes in plant floor layout dictate the need to alter fixture placement, this can be accomplished quickly and easily without re-gridding hassles. Simply change out the power cord for one of suitable length to reach the new location of the light.



Minimum Footprint




Driver Adjacent



#### PRODUCT WATTAGE & DIMENSIONS

WATTS	DIMENSIONS
100 Watts	11.0" Diameter x 1.9" Height
150 Watts	15.8" Diameter x 2.2" Height
200 Watts	15.8" Diameter x 2.2" Height
250 Watts	18.1" Diameter x 3.5" Height
300 Watts	18.1" Diameter x 3.5" Height





## **Turret Series LED**

**Specifications** 

#### **SPECIFICATIONS**

Power Factor	>0.9
	120/277V & 347/480V
Performance	Up to 144 lm/W
Operational Temperature	40° to 203°F
Distribution	120°
Mount Type	Suspension
Available Wattages	100W, 150W, 200W, 250W, 300W
Kelvin Temperature	4000K, 5000K
Color Rendering Index	>70

#### **FEATURES**

- > Patent-pending remote driver minimizes fixture operating temperature and allows fixture to evolve with changing plant floor demands with no re-gridding required
- > Inventronics Drivers with less than 1% failure rate
- > Dimmable 0-10V
- In-series transient voltage surge suppressor (TVSS) protects fixture against failure due to dirty power and power supply surges
- Available in high temperature (up to 203°F) or standard temperature (up to 120°F)
- > Optional motion sensor to maximize energy efficiency. Choose from standard by Wattstopper with L7 lens (fig 1.1 & fig 1.2\*), or Internet of Things (IOT) by Enlighted Sensors (fig 1.3).
- > UL 1598 listed
- > IP65 rated







#### **LUMINOUS OUTPUT**

Q WATTS //	LUMENS				
100 Watts	14,400 lumens				
150 Watts	21,600 lumens				
200 Watts	28,800 lumens				
250 Watts	36,000 lumens				
300 Watts	43,200 lumens				

#### POWER CORD (REQUIRED)

DESCRIPTION	PRODUCT NUMBER
125V, 15 amp, Straight Blade, 6 ft	PC-PP-125-15-SB-6
125V, 15 amp, Straight Blade, 12 ft	PC-PP-125-15-SB-12
125V, 15 amp, Twist Lock, 6 ft	PC-PP-125-15-TL-6
125V, 15 amp, Twist Lock, 12 ft	PC-PP-125-15-TL-12
125V, 20 amp, Twist Lock, 6 ft	PC-PP-125-20-TL-6
125V, 20 amp, Twist Lock, 12 ft	PC-PP-125-20-TL-12
250V, 20 amp, Twist Lock, 6 ft	PC-PP-250-20-TL-6
250V, 20 amp, Twist Lock, 12 ft	PC-PP-250-20-TL-12
277V, 15 amp, Twist Lock, 6 ft	PC-PP-277-15-TL-6
277V, 15 amp, Twist Lock, 12 ft	PC-PP-277-15-TL-12
277V, 20 amp, Twist Lock, 6 ft	PC-PP-277-20-TL-6
277V, 20 amp, Twist Lock, 12 ft	PC-PP-277-20-TL-12
480V, 20 amp, Twist Lock, 6 ft	PC-PP-480-20-TL-6
480V, 20 amp, Twist Lock, 12 ft	PC-PP-480-20-TL-12
600V, 20 amp, Twist Lock, 6 ft	PC-PP-600-20-TL-6
600V, 20 amp, Twist Lock, 12 ft	PC-PP-600-20-TL-12
600V, Whip, 6ft	PC-PP-600-W-6
600V, Whip, 12ft	PC-PP-600-W-12

SAMPLE ORDER NUMBER: TUR-5-100-40-1-2-1-1-1-X-X

8-250'

\*All Motion sensor purchases come as a set, including a motion sensor and an L7 Wattstopper lens.

#### TURRET ORDERING INFORMATION

SERIES	WATTAGE	KELVIN	OPTICS	LENS	FINISH	DRIVER VOLTAGE	REMOTE CABLE	MOTION SENSOR	BATTERY BACKUP
TUR-5 High Temp	100- (100W)	40- (4000K)	1- No Optics	2- Flat Poly Clear	1- Black	1- 120/277V	1- 3'	X- No	X- No
TUR-6 Standard Temp	150- (150W)	50- (5000K)		6- Flat Tempered Glass Clear		4- 347/480V	2- 10'	1- Standard*	1- Yes
	200- (200W)						3- 25'	2- Internet of Things*	
	250- (250W)						4- 50'		
	300- (300W)						5-100'		
							6- 150'		
							7- 200'		

<sup>\*</sup> Motion Sensor information: Standard (1) features sensors by Wattstopper with L7 lens. Internet of Things or IOT, (2) features sensors by Enlighted Sensors





### Veteran owned, so you can be confident we have your back





#### Tactik Labs is your added assurance of reliability.

Our LED lighting is designed to a higher standard. So is our validation process. At our in-house lab testing facility, our products undergo rigorous testing to provide you every assurance possible that all Tactik LED lighting will perform and last as promised. While others may talk about performance and reliability in harsh environments, Tactik Labs documents it.

#### Protecting you is second nature to us.

We protect distributors and customers with a 10-year warranty standard for added peace of mind. Plus, service after the sale includes a proactive warranty process – replacement is shipped immediately if a problem is identified and defective product is returned in its original box.





3115 N 21<sup>st</sup> Street, Suite 2, Sheboygan, WI 53083 920-287-3840 • sales@tactik.com

tactiklighting.com





