Permalife[®] Medium Voltage Cables for Nuclear Utility Applications



The science behind our medium voltage cables.

Permashield® non-conducting stress control layer

- 100% production tested in accordance with ICEA S-97-682.
- Greater than 2X reduction in electrical stress magnification caused by surface irregularities compared to semicon shields.
- 66% improvement in average AC breakdown strength over semicon. (Ref. A.D. Little, Inc., The Physics of Permashield[®], August 1983)

Kerite® discharge resistant insulation system

- Discharge resistant insulation system formulated to prevent the degradation that occurs as a result of partial discharge per ASTM D2275.
- Only medium voltage cable with zero reported failures of the insulation system. (Ref. NEI 06-05, Medium Voltage Underground Cable White Paper and EPRI Plant Engineering: Aging Management Program for Medium Voltage Cable systems for Nuclear Power Plants)

Helically applied tinned copper tape shield

- Greater flexibility, easier to handle and install, and simpler to splice and terminate than LCS shielded designs.
- Discharge resistant medium voltage cables never require partial discharge testing. Therefore, it is unnecessary to perform in-service partial discharge tests making the LCS design unnecessary for this cable.
- No adverse interaction between shield and insulation as reported for some discharge free insulations due to high coefficients of thermal expansion. (Ref. EPRI Cable Users Group Conference, August 2014, *Sixty-year Life Nuclear Cables for Gen III+ Reactor Applications*)

Performance history

- NEI 06-05 *Medium Voltage Underground Cable White Paper* concluded that "**81 units provided information on the number** of circuits in wet and dry applications" and "of the 20 units having brown EPR (Kerite), none had a failure of wet underground cable." It further went on to state that "no wet failures of brown EPR have been identified to-date."
- EPRI Plant Engineering: Aging Management Program Guidance for Medium-Voltage Cable Systems for Nuclear Power Plants, Revision 1 concluded that "brown EPR (Kerite) insulation, while being available to the early nuclear plants, continues to be produced. Approximately 20% of plants report its use. No water related failures have been reported in the nuclear industry to date."

Performance Standards

- Shielded cables are designed and tested in accordance with ICEA S-97-682 and ICEA S-93-639 or ICEA S-68-516 and AEIC CS-6
- Nonshielded cables are designed and tested in accordance with ICEA S-96-659
- Class 1E qualified in accordance with IEEE 383 and IEEE 323
- Nuclear qualified with a minimum of 60-year thermal life expectancy at 90°C (40-year life for Motor Lead Wire designs)
- Radiation resistance (up to 220 megarads)
- All cables pass IEEE 383-1974 as modified by NRC Reg Guide 1.131 vertical tray flame test

Fig. 1 Fig. 1 Electric Field, 1 mil from the flat interface Fig. 2 Electric Field, 5 mil from the flat interface 350 35 300 300 250 250 Semicor 200 200 150 150 100 100







- Quality Assurance program in accordance with 10 CFR 21 Appendix B
- Full traceability
- LSZH jacketed cable designs meet the low smoke generation requirements of UL 1685 and CSA FT4
- LSZH jacketed cable designs meet the halogen free requirements of ICEA S-93-639

Medium Voltage Product Guide



Construction

Conductor: Bare copper (tinned copper also available), class "B" compressed strand (compact strand also available) **Conductor Shield:** Permashield[®] conductor shield (non-conducting stress control layer)

Insulation: Proprietary Kerite® discharge resistant insulation

Insulation Shield: Thermoset semiconducting layer

Metallic Shield: 5 mil helically applied tinned copper tape with 20% overlap

Barrier Tape: Flame barrier tape(s)

Jacket: Heavy-duty chlorosulfonated polyethylene (CSPE) (available in black, blue, green, red, and yellow) (flexible, thermoset low smoke zero halogen (LSZH) also available)

5kV/8kV Single Conductor 115 Mil Insulation (133%/100%) and 140 Mil for 2000 kcmil and larger

Catalog No.	Size	Number of	O.D. Over	Jacket		Approx. Cable
Prefix	(AWG/kcmil)	Strands	Insulation (inch)	Thickness (mil)	O.D. (inch)	Weight (lb/M')
P45-0201	2/0	19	0.69	80	0.95	810
*P45-0401	4/0	19	0.80	80	1.06	1,110
*P45-0351	350	37	0.95	80	1.21	1,650
*P45-0501	500	37	1.10	80	1.36	2,200
*P45-0751	750	61	1.29	80	1.55	3,100
P45-1001	1000	61	1.44	110	1.76	4,100
P45-2001	2000	127	1.96	110	2.28	7,600

8kV Single Conductor 140 Mil Insulation (133%) and 175 Mil for 2000 kcmil and larger

Catalog No.	Size	Number of	O.D. Over	Jacket		Approx. Cable
Prefix	(AWG/kcmil)	Strands	Insulation (inch)	Thickness (mil)	O.D. (inch)	Weight (lb/M')
P45-0202	2/0	19	0.74	80	1.00	860
P45-0402	4/0	19	0.84	80	1.10	1,165
P45-0352	350	37	1.00	80	1.26	1,695
P45-0502	500	37	1.14	80	1.40	2,250
P45-0752	750	61	1.33	80	1.59	3,150
P45-1002	1000	61	1.48	110	1.80	4,150
P45-2002	2000	127	2.02	110	2.34	7,750

15kV Single Conductor 220 Mil Insulation (133%)

Catalog No.	Size	Number of	O.D. Over	Jacket		Approx. Cable
Prefix	(AWG/kcmil)	Strands	Insulation (inch)	Thickness (mil)	O.D. (inch)	Weight (lb/M')
P45-0200	2/0	19	0.88	80	1.14	1,000
P45-0400	4/0	19	0.99	80	1.25	1,325
P45-0350	350	37	1.14	80	1.40	1,865
P45-0500	500	37	1.29	80	1.55	2,450
P45-0750	750	61	1.48	110	1.80	3,500
P45-1000	1000	61	1.63	110	1.95	4,400
P45-2000	2000	127	2.10	110	2.42	7,900

25kV Single Conductor 320 Mil Insulation (133%)

Catalog No.	Size	Number of	O.D. Over	Jacket		Approx. Cable
Prefix	(AWG/kcmil)	Strands	Insulation (inch)	Thickness (mil)	O.D. (inch)	Weight (lb/M')
P45-0208	2/0	19	1.10	80	1.36	1,250
P45-0408	4/0	19	1.21	80	1.47	1,625
P45-0358	350	37	1.36	80	1.62	2,175
P45-0508	500	37	1.51	110	1.83	2,900
P45-0758	750	61	1.70	110	2.02	3,900
P45-1008	1000	61	1.85	110	2.17	4,800
P45-2008	2000	127	2.32	110	2.64	8,400

*Stock item.

Note: 100% insulation level available upon request. All gauge sizes and triplex constructions are available. Special designs are available on request. 25kV designs only qualified per IEEE 383-1974 and IEEE 323-1974.

Discharge Resistant Kerite® Insulation System

PermaLife[®] Nonshielded Medium Voltage Power Cable 5kV



5kV Single Conductor (100%) and (133%) Insulation Level

Catalog No.	Size	Number of	O.D. Over	Jacket		Approx. Cable
Prefix	(AWG/kcmil)	Strands	Insulation (inch)	Thickness (mil)	O.D. (inch)	Weight (Ib/M')
P45-3400	4/0	19	0.81	85	1.02	1,075
P45-3250	250	37	0.89	100	1.14	1,290
P45-3350	350	37	1.00	100	1.24	1,675
P45-3500	500	37	1.14	100	1.39	2,225
P45-3750	750	61	1.34	115	1.58	3,075
P45-3751	1000	61	1.48	115	1.72	3,925
P45-3752	2000	127	1.99	140	2.28	7,175

Note: All gauge sizes and triplex constructions are available.



Prefix	(AWG/kcmil)	O.D. (inch)	O.D. (inch)	(inch)	O.D. (inch)	Weight (lb/M')
P45-4306	6	0.65	1.41	1.97	2.08	2,210
P45-4302	2	0.76	1.64	2.19	2.30	2,910
P45-4340	4/0	1.02	2.21	2.66	2.79	5,200
P45-4325	250	1.14	2.45	2.95	3.08	6,150
P45-4335	350	1.24	2.68	3.16	3.31	7,450
P45-4350	500	1.39	2.99	3.46	3.60	9,500
P45-4375	750	1.58	3.45	4.27	4.42	12,650

Conductor

Note: Custom designs available upon request.

PermaLife[®] LSZH Motor Lead Wire Medium Voltage

Power Cable 7kV



Kerite[®] Insulation

7kV Single Conductor (100%) Insulation Level

•	• • •					
Catalog No.	Size	Number of	O.D. Over	Jac	ket	Approx. Cable
Prefix	(AWG/kcmil)	Strands	Insulation (inch)	Thickness (mil)	O.D. (Inch)	Weight (Ib/M [*])
P50-0060	6	19x7	0.51	70	0.68	295
P50-0040	4	19x7	0.56	70	0.73	365
P50-0020	2	37x7	0.63	70	0.80	470
P50-0010	1	37x7	0.67	70	0.84	535
P50-0100	1/0	37x7	0.71	70	0.88	556
P50-0200	2/0	37x7	0.76	70	0.93	735
P50-0300	3/0	37x7	0.82	85	1.01	910
P50-0400	4/0	37x7	0.93	85	1.09	1,075
P50-0250	250	61x7	0.99	100	1.21	1,290
P50-0350	350	61x7	1.08	100	1.30	1,675
P50-0500	500	61x7	1.25	100	1.47	2,225

Note: All gauge sizes and triplex constructions are available.

Committed to Nuclear Utilities



RSCC Nuclear Cables

With over 100 years of history designing and making the most reliable, highest performing cables for harsh and hazardous environments, RSCC Wire & Cable is the only cable maker in the US with 40 years of continuous service to the nuclear utility industry providing low and medium voltage cables and data cables — many with 40- to 60-year life cycle, as specified.

RSCC is now partnered with its sister company, **Kerite**, among the oldest, most reliable, and most recognized producer of medium voltage power cables for the nuclear, power gen, oil & gas, and other specialty industrial markets.



Kerite Company

The Kerite company manufactures medium and high voltage EPR insulated cables. It has manufactured cables since 1854. It's products range from 5kV to 138kV.

Kerite utilizes a proprietary cable design for its utility cables. The basic design is a unique discharge-resistant insulation system that is field proven and has the longest warranty in the industry.



Kerite Cable Services

For over 30 years Kerite Cable Services (KCS) has provided medium and high voltage solutions to satisfied clients in the electric utilities industry. These installations range in size from a few hundred feet, with congested substations, to several miles of transmission circuits.

A substation turnkey package from KCS provides the customer with the cable necessary for the project along with all required accessories, labor, and warranties.



RSCC World Class Nuclear Cable

For more information: 20 Bradley Park Road, East Granby, CT 06026 Tel: 860-653-8300 • Toll Free: 800-327-7625 Fax: 860-653-8301

