



Luminaire Strip

 Project: _____

 Location: _____

 Cat.No: _____

 Type: _____

 Notes: _____


The versatile Pila ST LED strip provides even distribution of light without pixilated glare. Its light weight, small profile, and simple installation make it easy to use and handle, and the light of choice for retail, light industrial, warehouse, and low bay applications.

Product offering

Catalog Code	Description	UPC Code	Case Qty. (pc/carton)	Pallet Qty. (pc/pallet)
ST422L40KU	4' Strip, 20W, 2200 LUMENS, 4000K, 120-277V	190096130863	1	108

Technical specifications

Nominal power	20W
Nominal lumens	2200 lumens
Input voltage	120-277V, 50/60Hz
CCT	4000K
CRI	>80
Power Factor (system)	>0.9
System Efficacy	>100 lm/W
Material and finishing	White painted finish, steel housing and wireway cover, extruded acrylic diffuser, polycarbonate diffuser end caps
Mounting	Ceiling mounted, bag parts included: wirenuts (3), wood screws (2), drywall anchor bolts (2)
Weight	2.7lb (1.2kg)
IP/IK rating	IP20 / IK02

Operating temperature range	-4F to 104°F (-20°C to 40°C)
Lifetime	30K hrs @ L70 B50 @ Ta 25°C
Compliance	cETLus listed for use in damp locations
Warranty	3-year limited warranty





Dimensions

