



E.B. Horsman & Son
The Electrical Distributor of Choice!

LEVITON®

Education Facility Solutions

LINE CARD



Power Connectivity

STRAIGHT BLADE RECEPTACLES

Heavy-Duty Industrial Specification Grade Receptacles

- 15 and 20 Amp – 125 and 250 Volt
- Standard or Decora Plus™
- GFCI, Tamper-Resistant, Isolated Ground and Weather-Resistant versions available




Commercial Specification Grade Receptacles

- 15 and 20 Amp – 125 and 250 Volt
- Standard or Decora Plus™
- Tamper-Resistant and Marked "Controlled" versions available



USB Receptacles

- 15 and 20 Amp – 125 and 250 Volt
- Combined total of 5.1A charging current and 25+ watts of power
- Built-in overcurrent protection helps protect electronics from receiving too much power, which can damage the device



SWITCHES

Toggle and Decora Plus™ Switches

- 20 Amp - 120/277 Volt
- Pilot Light, Illuminated and Tamper-Resistant versions available



Antimicrobial Treated Switches & Wallplates

- 20 Amp - 120/277 Volt
- Toggle, Decora Plus™, Conventional Wiring or Lev-Lok®
- Reduces 99.9% of the growth of harmful bacteria such as MRSA and E.coli, as well as many common staining and odor-causing bacteria, mold and fungi



WALLPLATES

Wallplates

- Available in Thermoplastic Nylon, Type 302 and 430 Stainless Steel, Aluminum and Brass
- Single and multi-gang configurations
- Antimicrobial Treated and Screwless versions available



LEV-LOK® MODULAR WIRING DEVICES

Lev-Lok Switches, Receptacles and Occupancy Sensors

- 3x faster installations and 5x faster swap outs than traditional wiring
- Traditional and Decora® Duplex, GFCI, Illuminated, MRI, USB, Marked Controlled Power Indication and Surge Protective Receptacles
- Single-Pole, Three-Way, Tamper-Resistant, Illuminated, and Antimicrobial Treated Switches
- Passive Infrared (PIR) and Multi-Technology (Ultrasonic and PIR) Occupancy Sensors*
- Mating Lev-Lok wiring module required for use



*Can be used to comply with ASHRAE 90.1, IECC and 2019 Title 24, Part 6 occupancy/vacancy sensing requirements

FLOOR BOXES

ALL ADA-COMPLIANT!

Floor Boxes

- 15 and 20 Amp – 125 Volt
- Single and multi-gang configurations
- Brass or Nickel-Plated faceplates available



Concrete Floor Boxes

- Round non-metallic floor box with a low voltage divider, concrete cover, and conduit reducers
- Can be used with finished floors made of wood, tile, vinyl, terrazzo, carpet and concrete
- Brushed Brass or Brush Nickel finished



Pop-Up Floor Box Receptacles

- Pre-wired terminal block for easy wiring access and installation
- Low profile cover recesses when not in use, reducing above-floor height to only ¼ inch
- Available in Brushed Nickel, Black, Brass, and Bronze finishes



Lighting Controls

WEATHERPROOF COVERS & BOXES

Weatherproof Device Covers & Boxes

- Available in 1-and 2-gang configurations
- Complies with the NEC® (2017) Section 406.9 for weatherproof enclosures in wet and damp locations
- Vertical or Horizontal Mounting



ELECTRICAL VEHICLE CHARGING

Evr-Green® Network Charging Stations

- Two Level 2 charging ports each supplying up to 7.2kW (208/240VAC @30A)
- SAE J1772™ Compliant
- Self-retracting cord management system



Evr-Green® Non-Network Charging Stations

- 20, 30, or 40 Amp
- SAE J1772™ Compliant
- RFID and 3rd party networking versions available



SURGE PROTECTION

Surge Protective Panels

- For single (split-phase) and 3-phase electrical systems
- Can be used to comply with National Electrical Code surge protection requirements



Surge Protective Receptacles

- 15 and 20 Amp - 125 Volt
- Single, Duplex and 4-in-1
- Point-of-use protection for up to 18,000 amps of surge current total
- Tamper-Resistant versions available



Measurement & Verification

SUBMETERING SOLUTIONS¹

VerifEye™ Meter Kits – Indoor & Outdoor

- 100 A - 5000 A, 120 V - 277/480 V
- Single Phase & Three Phase
- Isolated Pulse Output Standard
- NEMA 1 and 4X Enclosures
- Data collection hardware and BMO 3.0 energy information software available



OCCUPANCY SENSORS²

Decora® Wall Switch Multi-Technology Occupancy Sensors

- 120-277 V AC, 50/60Hz
- LED, Incandescent/Tungsten, Fluorescent
- UL and cUL Listed, ETL and cETL Listed



Ceiling-Mount Multi-Technology Occupancy Sensors

- Supports 24 V AC/DC power supplies
- Coverage Range: 500-2000 Sq. Ft.
- CUL/US, FCC and NOM Certified



Multi-Technology Wall or Corner Mount Occupancy Sensors

- Supports 24 V AC/DC power supplies
- Coverage: 1200 Sq. Ft.
- Adjustable swivel neck rotates 80° vertically and 60° horizontally
- CUL/US Certified



Fixture Mount PIR Sensors

- 120/277/347 V AC, 50/60Hz
- Indoor and outdoor models available
- IP65 models available
- Cold storage models available



RELAY PANELS²

GreenMAX®

- Cabinets with Short Circuit Current Rating (SCCR) of 25,000 A at 277 V AC
- Available in 8, 16, 32, or 48 relays
- Latching Relay Modules in 1-pole and 2-pole configurations
- LumaCAN and Ethernet network



EZ-MAX® Plus

- 120 V, 277 V and 347 V
- Available in 4 or 8 relays
- Standard 30 A Relay Card with Short Circuit Current Rating of 20,000 A



1 - Can be used to comply with ASHRAE 90.1 and 2019 Title 24, Part 6 service metering and disaggregation of electrical circuits requirements

2 - Can be used to comply with ASHRAE 90.1, and 2016 Title 24, Part 6 occupancy/vacancy sensing, 0-10V dimming, daylight harvesting, partial-ON, partial-OFF and demand response requirements

ROOM CONTROLS²

Provolt™ Room Controller (PRC) and App

- 120/277 V
- Self-contained device for occupancy sensing, 0-10 V dimming, daylight harvesting, partial-ON, partial-OFF, plug load control and demand response
- Configuration and control via the Provolt Bluetooth® mobile app
- Install with Provolt Keypad for manual control - 1, 2, or 4 button
- 1- or 2-zone control
- UL/cUL, CE, NOM, RoHS



Lumina™ RF Standalone Wireless Room Control System

- Delivers simple, scalable and flexible wireless control for any ON/OFF, 0-10V and phase cut dimming application
- Ideal for retrofits



2 - Can be used to comply with ASHRAE 90.1, and 2016 Title 24, Part 6 occupancy/vacancy sensing, 0-10V dimming, daylight harvesting, partial-ON, partial-OFF and demand response requirements

Integrated Room Control (IRC) Kit

- 120/277 V, 347 V
- Kit includes IRC, sensor, photocell and keypad for occupancy sensing, 0-10V dimming, daylight harvesting, partial-ON, partial-OFF and demand response
- Add OPP20 for plug load control
- 2- or 3-zone control
- UL/cUL Listed



Decora® Slide Dimmers

- For any type of load including LED and 0-10V
- Separate ON/OFF rocker switch allows you to set and keep preferred dimming level



IlumaTech® Dimmers

- For any type of load including LED and 0-10V
- Push button on/off preserves the selected brightness setting



SureSlide® Dimmers

- Integrated linear full range slide control for easy, precise operation
- Preset versions feature a separate on/off switch that preserves the selected brightness setting



Data Centers & Networking

NETWORK SOLUTIONS

Atlas-X1™ System

- Highest level of verified performance
- Supports high-bandwidth wireless networks
- Tool-free termination for fast deployment



Quickport® and 110-Style Patch Panels

- Industry's largest selection of patch panels
- Configurations for unique applications
- Multitude of port densities to support high-speed data applications



Opt-X® Unity Fiber Cabling System

- Premium fiber cabling system
- Reuse fiber backbone for migrations from 10 to 40, 100 and 400 Gb/s
- Ultra low loss connectivity allows longer distances and multiple connection points



IT/AV Control System

- Connects up to three sources to a single display
- No programming or user training required
- HDBaseT™-certified for product compatibility



Leviton Canada

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9
Telephone: 1-800-469-7890 • FAX: 1-800-563-1853
commercial@leviton.com
leviton.com/education

E. B. Horsman & Son

Telephone: 1-800-HORSMAN
info@ebhorsman.com
ebhorsman.com

