




www.buzonuk.com



Technical Data Sheet

U-E20

COMPONENTS

The U-E20 is composed of 1 piece

CHARACTERISTICS

Weight: 0,032 kg
Diameter: 149,25 mm
Thickness: 2 mm

MATERIAL

Material: SBR
Hardness Shore A Din 53505: 60-80 SHA
Color: Black
Density: 1,55 g/cm³
Temperature range: (-30)-+70C°
Tensile Strength Din 53504: 3 Mpa
Elongation at break DIN 53504: 250%

PACKAGING

Pieces per carton: 250 pcs
Carton weight: 8,50 kg
Carton dimension: 400 x 290 x 150 mm
Cartons per pallet: 40 pcs
Pieces per pallet: 10 000 pcs
Pallet dimensions: 100 x 120 x 220 cm

APPLICATIONS

Designed so full, half or quarter piece of the Buzon shim can be used. For use with marble, stone, granite, ceramic tiles and to obtain a better anti-slip and acoustic performance, as well as shock absorption. Use in combination with the Buzon U-E10 shim, to compensate for irregularities in the thickness of paving materials.

SAFETY INSTRUCTIONS

Buzon pedestals are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.

