



Technical Data Sheet

U-WALL

COMPONENTS

The U-WALL is composed of 1 piece

CHARACTERISTICS

Weight: **0,038 kg**

Additional height: **3 mm**

Suitable for use with 6mm tabs or smaller

MATERIAL

Copolymer polypropylene (CPP)

Composition: +/- **80%** first grade pre-selected recycled PPC, and +/- **20%** Talc + Masterbatch black

Designed and manufactured in Europe

Use of recycled materials exclusively of EU origin

Resistant to weathering, sea salts, algae and a wide range of chemicals

Temperature range: **-30 C° to +80 C°**

PACKAGING

Pieces per carton: **pcs**

Carton weight: **kg**

Carton dimension: **mm**

Cartons per pallet: **pcs**

Pieces per pallet: **pcs**

Pallet dimensions: **cm**

APPLICATIONS

Maintains a regular space between the paver and the wall for proper water drainage.

Accessories are available for applications with various outdoor finishes, such as granite stone pavers, composite / timber decking, ceramic tiles and fibreglass or metal grating panels.

SAFETY INSTRUCTIONS

Buzon pedestals are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.

