





Technical Data Sheet-BC FR

BC-0-FR (Fire Resistant)

11mm Non adjustable

CHARACTERISTICS

Top: ø 160 mm, 201 cm² Base: ø 200 mm, 314 cm²

Weight: **0,073 kg** Non Adjustable

With addition of BC-PH5 slope corrector, the height is 25mm

MATERIAL

Manufactured with Copolymer of Polypropylene (CPP) and fire retardant additives.

The fire-rated version of our Buzon BC-FR series of pedestals meets the European and the United Kingdom EN 13501 standard to achieve Bfl-S1 classification.

Classification: Bfl-S1

Standard(s): EN 13501-1 & EN 45545-2

PACKAGING


Pieces per carton: 294 pcs Carton weight: 22,36 kg

Carton dimension: 600 x 400 x 410 mm

Cartons per pallet: **25 pcs**Pieces per pallet: **7 350 pcs**

Pallet dimensions: 100 x 120 x 220 cm







APPLICATIONS

Buzon BC-FR is manufactured with Fire Retardant additives and can be used, depending on the local requirements, for a wider range of applications, such as terraces, pool decks, and water features and in landscape areas and on rooftops.

Circular Tabs







BC-Kit5-FR





COMPRESSION TEST*

Performed on the full (1/1), half (1/2) and quarter (1/4) surface of the head (1kN=100 kg=224,8 lbF)

Position	Height (mm)	Breaking load (kN)	Breaking load (lbF)
1/1	11	30,70 (3700 kg)	6 906
1/2	11	17 (1700 kg)	4 001
1/4	11	10 (1000 kg)	2 248

^{*} Tests carried out by SIRRIS

SAFETY INSTRUCTIONS

Buzon pedestals are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.

sales@buzonuk.com +44 (0)20 8614 0874

Buzon has a policy of continuous improvement and reserves the right to modify, revise or change the above specifications without notice. This brochure is for descriptive purpose only and is based on the product as on the date of publication of this information.