



PQube® 3 Power Analyzer Demo Kit

Perfect for trade shows, hands-on training sessions. Show your customers how the PQube 3 Power Analyzer is compact, easy-to-use, and versatile.

INCLUDED WITH EACH KIT:

PQube 3 Power Analyzer

- 4 voltage and 8 current channels
- 32GB internal memory
- 4 analog inputs
- 1 digital input
- 1 relay output
- Ethernet, USB, SD (includes 16 GB micro-SD card)
- Power Quality Class A Ed3
- 4-quadrant revenue grade Energy Class 0.2
- 512 samples/cycles, H F transients 4Mhz, 2kHz~|50kHz conducted emissions
- Monitors up to two 3-phase circuits

Cables and Accessories

- 5A high accuracy split-core current sensor (CT)
- Shielded for noise immunity
- Hinge top, SA:333mV, rated 600V, 40-600Hz,
- 0.4"x0.4" opening
- Power cable
- AC plug adapter - select appropriate version for your region
- Ethernet cable
- USB cable for use with the ENV2 probe
- USB thumb drive

PM2 Module

- Plug-in instrument power manager
- Powers PQube 3 at 100 to 240VAC, 50/60Hz
- Provides 24V DC for accessories (max SW)

UPS1 Module

- Plug-in uninterruptable power supply (UPS)
- Up to 30 minutes of back-up power to PQube 3.

CTI-5A

- Current input module
- For interfacing to existing 5A metering CTs

ENV2 Module

- EnviroSensor probe - ambient temperature, Humidity, barometric pressure, axis acceleration
- Plugs into USB port

Carrying Case

- Waterproof (IP67)
- Dimensions: 14.3" x 11.1" x 4.7" (363mm x 282mm x 120mm)
- Replaceable internal foam
- DIN rail plate included

EC&M
Product of the Year
2018 Category Winner



Contact Us

info@powerside.com
powerside.com



Canada

7850 Trans-Canada Highway
Saint-Laurent (QC) H4T 1A5
1 (877) 333-8392

United States

980 Atlantic Ave
Alameda (CA) 94501
1 (888) 736-4347