

## Modular Access Control (MAC) Portal Specification Sheet

### MAC Safe-T-Check

#### General Features:

Enclosure	10' Container
Approx. Shipping Weight*	4,900 lbs
Approx. Footprint (L X W)	10'-0" X 8'-0"
Approx. Shipping (L X W X H)*	10'-0" X 8'-5" X 8'-6"
Approx. Overall (L X W X H)*	10'-0" X 9'-11" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	Yes
Other	No

#### Office:

Approx. Dimensions (L X W)	9'-1" X 7'-1"
Cooling Capacity / BTUH	20,000
Heating Capacity / BTUH	13,000
Heating Watts	3,800
Wall / Ceiling Insulation	R-10
Entry Door with Window	Vinyl Strips - Amber

#### Turnstile Bay:

Lanes	1
Lane Style	Single
Roll-Up Doors	3' per Single

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	40
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	5.3
Demand Amps	22



Model No. M1ST



#### Patents:

US 10,626,629 B2

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.

