

## Modular Access Control (MAC) Portal Specification Sheet

### MAC-1 Lite

#### General Features:

Enclosure	Custom
Approx. Shipping Weight*	1,300 lbs
Approx. Footprint (L X W)	6'-0" X 6'-0"
Approx. Shipping (L X W X H)*	6'-0" X 6'-7" X 8'-5"
Approx. Overall (L X W X H)*	6'-0" X 6'-7" X 8'-5"

#### Lifting Methods:

Bottom Corner Blocks	No
Top Corner Blocks	No
Fork Lift	Yes
Other	No

#### Office:

Approx. Dimensions (L X W)	n/a
Cooling Capacity / BTUH	n/a
Heating Capacity / BTUH	n/a
Heating Watts	n/a
Wall / Ceiling Insulation	n/a
Entry Door with Window	n/a

#### Turnstile Bay:

Lanes	1
Lane Style	Single
Roll-Up Doors	n/a

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	MLO
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	0.8
Demand Amps	3



#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



## Modular Access Control (MAC) Portal Specification Sheet

### MAC-1

#### General Features:

Enclosure	Custom
Approx. Shipping Weight*	3,500 lbs
Approx. Footprint (L X W)	8'-0" X 6'-0"
Approx. Shipping (L X W X H)*	9'-6" X 6'-6" X 8'-6"
Approx. Overall (L X W X H)*	9'-6" X 6'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	No
Fork Lift	Yes
Other	Top Lifting Lugs

#### Office:

Approx. Dimensions (L X W)	n/a
Cooling Capacity / BTUH	n/a
Heating Capacity / BTUH	n/a
Heating Watts	n/a
Wall / Ceiling Insulation	n/a
Entry Door with Window	n/a

#### Turnstile Bay:

Lanes	1
Lane Style	Single
Roll-Up Doors	3' per Single

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	1.4
Demand Amps	6



Model No. M1XX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



## Modular Access Control (MAC) Portal Specification Sheet

### MAC-2

#### General Features:

Enclosure	20' Container
Approx. Shipping Weight*	7,200 lbs
Approx. Footprint (L X W)	20'-0" X 8'-0"
Approx. Shipping (L X W X H)*	20'-0" X 8'-10" X 8'-6"
Approx. Overall (L X W X H)*	20'-0" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	Yes
Other	No

#### Office:

Approx. Dimensions (L X W)	7'-6" X 7'-0"
Cooling Capacity / BTUH	12,000
Heating Capacity / BTUH	11,000
Heating Watts	3,500
Wall / Ceiling Insulation	R-13
Entry Door with Window	1

#### Turnstile Bay:

Lanes	2
Lane Style	Single
Roll-Up Doors	3' per Single

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	6.4
Demand Amps	26

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



Model No. M2MX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737



## Modular Access Control (MAC) Portal Specification Sheet

### MAC-2

#### General Features:

Enclosure	20' Container
Approx. Shipping Weight*	7,300 lbs
Approx. Footprint (L X W)	20'-0" X 8'-0"
Approx. Shipping (L X W X H)*	20'-6" X 8'-4" X 8'-6"
Approx. Overall (L X W X H)*	20'-6" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	Yes
Other	No

#### Office:

Approx. Dimensions (L X W)	7'-11" X 7'-0"
Cooling Capacity / BTUH	12,000
Heating Capacity / BTUH	11,000
Heating Watts	3,500
Wall / Ceiling Insulation	R-13
Entry Door with Window	1

#### Turnstile Bay:

Lanes	2
Lane Style	Single
Roll-Up Doors	3' per Single

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	MLO
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	6.4
Demand Amps	26

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



Model No. M2EX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737





## Modular Access Control (MAC) Portal Specification Sheet

### MAC-2T Lite

#### General Features:

Enclosure	Custom
Approx. Shipping Weight*	2,300 lbs
Approx. Footprint (L X W)	8'-7" X 6'-0"
Approx. Shipping (L X W X H)*	6'-0" X 9'-3" X 8'-5"
Approx. Overall (L X W X H)*	6'-0" X 9'-3" X 8'-5"

#### Lifting Methods:

Bottom Corner Blocks	No
Top Corner Blocks	No
Fork Lift	Yes
Other	No

#### Office:

Approx. Dimensions (L X W)	n/a
Cooling Capacity / BTUH	n/a
Heating Capacity / BTUH	n/a
Heating Watts	n/a
Wall / Ceiling Insulation	n/a
Entry Door with Window	n/a

#### Turnstile Bay:

Lanes	2
Lane Style	Tandem
Roll-Up Doors	n/a

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	MLO
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	0.9
Demand Amps	4

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



Model No. M2LX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737



## Modular Access Control (MAC) Portal Specification Sheet

### MAC-2T

#### General Features:

Enclosure	10' Container
Approx. Shipping Weight*	4,600 lbs
Approx. Footprint (L X W)	10'-0" X 8'-0"
Approx. Shipping (L X W X H)*	10'-6" X 8'-2" X 8'-6"
Approx. Overall (L X W X H)*	10'-6" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	Yes
Other	No

#### Office:

Approx. Dimensions (L X W)	n/a
Cooling Capacity / BTUH	n/a
Heating Capacity / BTUH	n/a
Heating Watts	n/a
Wall / Ceiling Insulation	n/a
Entry Door with Window	n/a

#### Turnstile Bay:

Lanes	2
Lane Style	Tandem
Roll-Up Doors	6' per Tandem

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	1.4
Demand Amps	6

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



Model No. M2TX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737



## Modular Access Control (MAC) Portal Specification Sheet

### MAC-3

#### General Features:

Enclosure	20' Container
Approx. Shipping Weight*	6,700 lbs
Approx. Footprint (L X W)	20'-0" X 8'-0"
Approx. Shipping (L X W X H)*	20'-4" X 8'-2" X 8'-6"
Approx. Overall (L X W X H)*	20'-4" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	No
Other	No

#### Office:

Approx. Dimensions (L X W)	n/a
Cooling Capacity / BTUH	n/a
Heating Capacity / BTUH	n/a
Heating Watts	n/a
Wall / Ceiling Insulation	n/a
Entry Door with Window	n/a

#### Turnstile Bay:

Lanes	3
Lane Style	Single
Roll-Up Doors	3' per Single

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	2.1
Demand Amps	26



Model No. M3XX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.





## Modular Access Control (MAC) Portal Specification Sheet

### MAC-3o

#### General Features:

Enclosure	26' Container
Approx. Shipping Weight*	8,600 lbs
Approx. Footprint (L X W)	26'-0" X 8'-0"
Approx. Shipping (L X W X H)*	26'-6" X 8'-6" X 8'-6"
Approx. Overall (L X W X H)*	26'-6" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	No
Other	No

#### Office:

Approx. Dimensions (L X W)	9'-1" X 7'-0"
Cooling Capacity / BTUH	9,000
Heating Capacity / BTUH	11,000
Heating Watts	3,500
Wall / Ceiling Insulation	R-13
Entry Door with Window	2

#### Turnstile Bay:

Lanes	3
Lane Style	Single
Roll-Up Doors	3' per Single

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	7.5
Demand Amps	31

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



Model No. M3EX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737





## Modular Access Control (MAC) Portal Specification Sheet

### MAC-4

#### General Features:

Enclosure	40' Container
Approx. Shipping Weight*	15,500 lbs
Approx. Footprint (L X W)	40'-0" X 8'-0"
Approx. Shipping (L X W X H)*	40'-6" X 8'-6" X 8'-6"
Approx. Overall (L X W X H)*	40'-6" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	Yes
Other	No

#### Office:

Approx. Dimensions (L X W)	17'-2" X 7'-0"
Cooling Capacity / BTUH	12,000
Heating Capacity / BTUH	11,000
Heating Watts	3,500
Wall / Ceiling Insulation	R-13
Entry Door with Window	2

#### Turnstile Bay:

Lanes	4
Lane Style	Single
Roll-Up Doors	3' per Single

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	7.7
Demand Amps	32

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



Model No. M4MX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737



## Modular Access Control (MAC) Portal Specification Sheet

### MAC-4

#### General Features:

Enclosure	40' Container
Approx. Shipping Weight*	15,500 lbs
Approx. Footprint (L X W)	40'-0" X 8'-0"
Approx. Shipping (L X W X H)*	40'-6" X 8'-6" X 8'-6"
Approx. Overall (L X W X H)*	40'-6" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	Yes
Other	No

#### Office:

Approx. Dimensions (L X W)	17'-7" X 7'-0"
Cooling Capacity / BTUH	12,000
Heating Capacity / BTUH	11,000
Heating Watts	3,500
Wall / Ceiling Insulation	R-13
Entry Door with Window	2

#### Turnstile Bay:

Lanes	4
Lane Style	Single
Roll-Up Doors	3' per Single

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	MLO
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	7.5
Demand Amps	31



Model No. M4EX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



## Modular Access Control (MAC) Portal Specification Sheet

### MAC-4T

#### General Features:

Enclosure	20' Container
Approx. Shipping Weight*	7,200 lbs
Approx. Footprint (L X W)	20'-0" X 8'-0"
Approx. Shipping (L X W X H)*	20'-4" X 8'-2" X 8'-6"
Approx. Overall (L X W X H)*	20'-4" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	Yes
Other	No

#### Office:

Approx. Dimensions (L X W)	n/a
Cooling Capacity / BTUH	n/a
Heating Capacity / BTUH	n/a
Heating Watts	n/a
Wall / Ceiling Insulation	n/a
Entry Door with Window	n/a

#### Turnstile Bay:

Lanes	4
Lane Style	Tandem
Roll-Up Doors	6' per Tandem

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	2.1
Demand Amps	9



Model No. M4TX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.





## Modular Access Control (MAC) Portal Specification Sheet

### MAC-5

#### General Features:

Enclosure	40' Container
Approx. Shipping Weight*	16,000 lbs
Approx. Footprint (L X W)	40'-0" X 8'-0"
Approx. Shipping (L X W X H)*	40'-6" X 8'-6" X 8'-6"
Approx. Overall (L X W X H)*	40'-6" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	Yes
Other	No

#### Office:

Approx. Dimensions (L X W)	17'-7" X 7'-0"
Cooling Capacity / BTUH	12,000
Heating Capacity / BTUH	11,000
Heating Watts	3,500
Wall / Ceiling Insulation	R-13
Entry Door with Window	2

#### Turnstile Bay:

Lanes	5
Lane Style	Single
Roll-Up Doors	3' per Single

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	MLO
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	8.2
Demand Amps	34



Model No. M5MX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



## Modular Access Control (MAC) Portal Specification Sheet

### MAC-6

#### General Features:

Enclosure	40' Container
Approx. Shipping Weight*	15,200 lbs
Approx. Footprint (L X W)	40'-0" X 8'-0"
Approx. Shipping (L X W X H)*	40'-0" X 8'-4" X 8'-6"
Approx. Overall (L X W X H)*	40'-0" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	Yes
Other	No

#### Office:

Approx. Dimensions (L X W)	6'-9" X 7'-0"
Cooling Capacity / BTUH	9,000
Heating Capacity / BTUH	11,000
Heating Watts	3,500
Wall / Ceiling Insulation	R-13
Entry Door with Window	1

#### Turnstile Bay:

Lanes	6
Lane Style	Single
Roll-Up Doors	3' per Single

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	8.0
Demand Amps	33



Model No. M6MX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



## Modular Access Control (MAC) Portal Specification Sheet

### MAC-6T

#### General Features:

Enclosure	25' Container
Approx. Shipping Weight*	9,300 lbs
Approx. Footprint (L X W)	25'-0" X 8'-0"
Approx. Shipping (L X W X H)*	25'-8" X 8'-2" X 8'-6"
Approx. Overall (L X W X H)*	25'-8" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	No
Other	No

#### Office:

Approx. Dimensions (L X W)	n/a
Cooling Capacity / BTUH	n/a
Heating Capacity / BTUH	n/a
Heating Watts	n/a
Wall / Ceiling Insulation	n/a
Entry Door with Window	n/a

#### Turnstile Bay:

Lanes	6
Lane Style	Tandem
Roll-Up Doors	6' per Tandem

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	3.6
Demand Amps	15



Model No. M6TX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.





## Modular Access Control (MAC) Portal Specification Sheet

### MAC-8T

#### General Features:

Enclosure	40' Container
Approx. Shipping Weight*	13,800 lbs
Approx. Footprint (L X W)	40'-0" X 8'-0"
Approx. Shipping (L X W X H)*	40'-0" X 8'-4" X 8'-6"
Approx. Overall (L X W X H)*	40'-0" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	No
Other	No

#### Office:

Approx. Dimensions (L X W)	6'-5" X 7'-0"
Cooling Capacity / BTUH	9,000
Heating Capacity / BTUH	11,000
Heating Watts	3,500
Wall / Ceiling Insulation	R-13
Entry Door with Window	1

#### Turnstile Bay:

Lanes	8
Lane Style	Tandem
Roll-Up Doors	6' per Tandem

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	7.7
Demand Amps	32

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.



Model No. M8TX

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737



## Modular Access Control (MAC) Portal Specification Sheet

### MAC-10T

#### General Features:

Enclosure	40' Container
Approx. Shipping Weight*	14,500 lbs
Approx. Footprint (L X W)	40'-0" X 8'-0"
Approx. Shipping (L X W X H)*	40'-10" X 8'-2" X 8'-6"
Approx. Overall (L X W X H)*	40'-10" X 9'-6" X 8'-6"

#### Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	No
Other	No

#### Office:

Approx. Dimensions (L X W)	n/a
Cooling Capacity / BTUH	n/a
Heating Capacity / BTUH	n/a
Heating Watts	n/a
Wall / Ceiling Insulation	n/a
Entry Door with Window	n/a

#### Turnstile Bay:

Lanes	10
Lane Style	Tandem
Roll-Up Doors	6' per Tandem

#### Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	6.4
Demand Amps	27



Model No. M10T

#### Patents:

US 7,762,025; CA 2,587,968;  
EP 1812666; DZ 5173;  
EG 25627; US 8,015,754;  
US 8,671,624; US 9,051,748;  
US 9,404,278; US 7,823,338;  
CA 2,682,764; EP 2137356;  
NG RPNG/C/2007/737

\* General feature weights and dimensions are calculated and can vary based on container and options.

\*\* Standard voltage, other voltages are available.

\*\*\* Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.

