

Modular Guard Booth Specification Sheet

GH-82

General Features:

| | |
|-------------------------------|------------------------|
| Enclosure | 20' Container |
| Approx. Shipping Weight* | 7,900 lbs |
| Approx. Shipping (L X W X H)* | 20'-3" X 8'-6" X 8'-6" |

Lifting Methods:

| | |
|----------------------|-----|
| Bottom Corner Blocks | Yes |
| Top Corner Blocks | Yes |
| Fork Lift | Yes |
| Other | No |

Office:

| | |
|----------------------------|----------------|
| Approx. Dimensions (L X W) | 18'-6" X 7'-0" |
| Cooling Capacity / BTUH | 12,000 |
| Heating Capacity / BTUH | 11,000 |
| Heating Watts | 3,500 |
| Wall / Ceiling Insulation | R-15 |
| Entry Door with Window | 2 |

Electrical Data:

| | |
|-----------------------|---------|
| Lighting Technology | LED |
| Load Center Main Amps | 100 |
| Voltage** | 120/240 |
| Frequency | 60 Hz |
| Demand KVA*** | 6.3 |
| Demand Amps | 26 |



Model No. G82X



* General feature weights and dimensions are calculated and can vary based on container and options.

** Standard voltage, other voltages are available.

*** Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.

