

Modular Access Control (MAC) Portal Specification Sheet

MAC-2L

General Features:

Enclosure	Custom
Approx. Shipping Weight*	2,400 lbs
Approx. Footprint (L X W)	8'-11" X 6'-0"
Approx. Shipping (L X W X H)*	9'-3" X 6'-0" X 8'-5"
Approx. Overall (L X W X H)*	9'-3" X 6'-0" X 8'-5"

Lifting Methods:

Bottom Corner Blocks	No
Top Corner Blocks	No
Fork Lift	Yes
Other	No

Office:

Approx. Dimensions (L X W)	n/a
Cooling Capacity / BTUH	n/a
Heating Capacity / BTUH	n/a
Heating Watts	n/a
Wall / Ceiling Insulation	n/a
Entry Door with Window	n/a

Turnstile Bay:

Lanes	2
Lane Style	Tandem
Roll-Up Doors	n/a

Electrical Data:

Lighting Technology	LED
Load Center Main Amps	125
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	0.9
Demand Amps	4



Model No. M2LX

Patents:

US 7,762,025; CA 2,587,968;
EP 1812666; DZ 5173;
EG 25627; US 8,015,754;
US 8,671,624; US 9,051,748;
US 9,404,278; US 7,823,338;
CA 2,682,764; EP 2137356;
NG RPNG/C/2007/737

* General feature weights and dimensions are calculated and can vary based on container and options.

** Standard voltage, other voltages are available.

*** Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.

