

Modular Access Control (MAC) Portal Specification Sheet

MAC-6M

General Features:

| | |
|-------------------------------|------------------------|
| Enclosure | 40' Container |
| Approx. Shipping Weight* | 15,200 lbs |
| Approx. Footprint (L X W) | 40'-0" X 8'-0" |
| Approx. Shipping (L X W X H)* | 40'-0" X 8'-6" X 8'-6" |
| Approx. Overall (L X W X H)* | 40'-0" X 9'-6" X 8'-6" |

Lifting Methods:

| | |
|----------------------|-----|
| Bottom Corner Blocks | Yes |
| Top Corner Blocks | Yes |
| Fork Lift | No |
| Other | No |

Office:

| | |
|----------------------------|---------------|
| Approx. Dimensions (L X W) | 6'-9" X 7'-0" |
| Cooling Capacity / BTUH | 9,000 |
| Heating Capacity / BTUH | 11,000 |
| Heating Watts | 3,500 |
| Wall / Ceiling Insulation | R-15 |
| Entry Door with Window | 1 |

Turnstile Bay:

| | |
|---------------|---------------|
| Lanes | 6 |
| Lane Style | Single |
| Roll-Up Doors | 3' per Single |

Electrical Data:

| | |
|-----------------------|-----------|
| Lighting Technology | LED |
| Load Center Main Amps | 100 |
| Voltage** | 120 / 240 |
| Frequency | 60 Hz |
| Demand KVA*** | 9.2 |
| Demand Amps | 38 |



Model No. M6MX

Patents:

US 7,762,025; CA 2,587,968;
EP 1812666; DZ 5173;
EG 25627; US 8,015,754;
US 8,671,624; US 9,051,748;
US 9,404,278; US 7,823,338;
CA 2,682,764; EP 2137356;
NG RPNG/C/2007/737

* General feature weights and dimensions are calculated and can vary based on container and options.

** Standard voltage, other voltages are available.

*** Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.

