

Modular Access Control (MAC) Portal Specification Sheet

MAC-8E

General Features:

Enclosure	40' Container
Approx. Shipping Weight*	13,700 lbs
Approx. Footprint (L X W)	40'-0" X 8'-0"
Approx. Shipping (L X W X H)*	40'-8" X 8'-4" X 8'-6"
Approx. Overall (L X W X H)*	40'-8" X 9'-6" X 8'-6"

Lifting Methods:

Bottom Corner Blocks	Yes
Top Corner Blocks	Yes
Fork Lift	No
Other	No

Office:

Approx. Dimensions (L X W)	6'-9" X 7'-0"
Cooling Capacity / BTUH	9,000
Heating Capacity / BTUH	11,000
Heating Watts	3,500
Wall / Ceiling Insulation	R-15
Entry Door with Window	1

Turnstile Bay:

Lanes	8
Lane Style	Tandem
Roll-Up Doors	6' per Tandem

Electrical Data:

Lighting Technology	LED
Load Center Main Amps	100
Voltage**	120 / 240
Frequency	60 Hz
Demand KVA***	10.1
Demand Amps	42



Model No. M8EX

Patents:

US 7,762,025; CA 2,587,968;
EP 1812666; DZ 5173;
EG 25627; US 8,015,754;
US 8,671,624; US 9,051,748;
US 9,404,278; US 7,823,338;
CA 2,682,764; EP 2137356;
NG RPNG/C/2007/737

* General feature weights and dimensions are calculated and can vary based on container and options.

** Standard voltage, other voltages are available.

*** Demand KVA is based on National Electric Code (NEC) load calculation methods, actual may vary depending on customer equipment.

