



www.AirPacInc.com

**SPECS AT A GLANCE**  
**Cooling, Heating**  
**and Ventilating Equipment**  
**SALES AND RENTALS**

(Office) 540-635-5011

(Cell) 540-671-0679

AirPac Technology Park  
 888 Shenandoah Shores Rd.  
 Front Royal, VA 22630 USA



**PORTABLE AIR CONDITIONERS**

Rent spot coolers! AIRPAC PORTABLE AIR CONDITIONERS <i>American Engineered. American Made. That's Cool!</i>	SPOTHVAC	COOLIT® Series		PORTAPAC® Series			
	SpotHVAC	COOLIT2600	COOLIT3300	PAC36	PAC60	PAC96	PAC120
<b>BTU/h Cool/Heat</b>	14,000 - 11,000	13,500 - N/A	28,000 - N/A	36,000 - N/A	60,000 - N/A	96,000 - N/A	120,000 - N/A
<b>Power Requirements</b> <i>(Multiple choices for PAC's)</i>	115V	115V	208/230/1/60Hz	208/230/1/60Hz 208/230/3/60Hz 460/480/3/60Hz	208/230/1/60Hz 208/230/3/60Hz 460/480/3/60Hz	208/230/3/60Hz 460/480/3/60Hz	208/230/3/60Hz 460/480/3/60Hz
<b>Amp Rating</b>	10.8	11.7	16.0	41 @ 208/1 26 @ 208/3 12 @ 460/3	59 @ 208/1 34 @ 208/3 18 @ 480/3	50 @ 208/3 26 @ 480/3	64 @ 208/3 32 @ 480/3
<b>Fuse Size (amps)</b>	15	15	20	60 @ 208/1 35 @ 208/3 15 @ 460/3	80 @ 208/1 60 @ 208/3 25 @ 480/3	70 @ 208/3 35 @ 480/3	90 @ 208/3 45 @ 480/3
<b>Supp Air Flow high/med/low</b>	456/396/336	440	1,100	1,200	2,000	3,200	4,000
<b>Return/Condenser CFM Max</b>	N/A	680	2,050	2,200	3,100	4,500	6,200
<b>Dimensions w x d x h (in.)</b>	24 x 23-1/2 x 43	18-3/4 x 32-3/4 x 47-1/2	35-1/2 x 24 x 55	42 x 28-3/4 x 63-3/8	42 x 28-3/4 x 63-3/8	47-3/4 x 28-3/4 x 77	60-1/4 x 29-1/4 x 79-1/4
<b>Weight (lbs.)</b>	130	188	405	650	750	1,050	1,300
<b>Control Features</b> Control Panel/Thermostat	Electronic	<b>Standard:</b> Off - Fan - Cool <b>Option 1:</b> Electronic Thermostat with LCD Display <b>Option 2:</b> Electronic Programmable Thermostat with LCD Display <b>Option 3:</b> Electronic Programmable Thermostat with Internet Capability					
<b>Cabinet Style</b>	0.06" Aluminum	18 ga. galv.	16 ga. galv.	16 ga. galv.	16 ga. galv.	16 ga. galv.	16 ga. galv.
<b>Cabinet Finish</b>	Diamond Tread	ABS Plastic	Powder Coated	Powder Coated	Powder Coated	Powder Coated	Powder Coated
<b>NEMA Plug/Cord Length (ft.)</b>	5-15P / 6	5-15P / 6	L6-20 / 5.5	Hard Wired	Hard Wired	Hard Wired	Hard Wired
<b>Supp/Evap &amp; Ret/Cond Air Size (in. dia.)</b>	6 - 6	N/A - 10	N/A - 10	16 - 16	16 - 16	18 - 18	20 - 20
<b>Supp/Evap Max. Ext. Static (IWG)</b>	N/A	0.5	0.8	1.0	1.0	1.5	1.5
<b>Supp/Evap &amp; Ret/Cond Max Duct Length (ft.)</b>	5 - 12	N/A - 25	N/A - 50	25 - 50	25 - 50	25 - 50	25 - 50
<b>Condensate Management</b>	Internal Pump	--2 Tanks, 2.5 gal. ea. & Internal Tank--		----- Internal Pump -----			
<b>Condensate Pump Lift (ft.)/Discharge ID (in.)</b>	65 - 1/4	20 - 3/8	20 - 3/8	20 - 3/8	20 - 3/8	20 - 3/8	20 - 3/8
<b>Max. dB w/ Condenser Duct</b>	N/A	52	58	N/A	N/A	N/A	N/A
<b>Refrigerant Type/Charge per system (oz.)</b>	R-410A / 21.1	R-410A / 18	R-410A / 48	R-410A / 80	R-410A / 88	R-410A / 88	R-410A / 88
<b>Safety Certification</b>	UL Listed	-----ETL-Electrical Testing Laboratory-----					

**PORTABLE HEATERS**

Rent clean, safe electric heat!	HEATIT™ Series			HEATPAC™ Series		
	HEATIT1.5	HEATIT3	HEATIT6/HEATIT9	HEATPAC18	HEATPAC40	HEATPAC60
<b>Heating Capacity</b>					14" Flange for Optional Duct	14" Flange for Optional Duct
kW	1.5	3	6/9	18	40	60
BTU/h	5,100	10,200	20,500/30,700	45,000/65,000	51,200/102,400/136,500	82,000 /164,000/205,000
Watts	1,500	3,000	6,000/9,000	13,000/19,000	16,000/32,000/40,000	24,000/48,000/60,000
<b>Electrical Data</b>						
Voltage	120/60/1	240/60/1	240/60/1	240/60/3	480/60/3	480/60/3
Power Consumption (amps)	12.5	12.5	25/37.5	31/47	20/40/50	30/60/75
Power Cord Gauge (AWG)	3 x 16	3 x 16	3 x 8	N/A	N/A	N/A
Cord Length (ft.)	9	9	----- Hard Wired -----			
Power Connection	NEMA 5-15P	NEMA 6-20P	----- Hard Wired/CAM -----			
<b>Airflow (CFM)</b>	116	205	350	590	1765	1765
<b>Dimensions</b>						
w x d x h (in.)	8 x 12 x 12	10 x 14 x 15	12 x 23 x 18	14 x 30 x 18	20 x 46 x 25	20 x 46 x 25
<b>Weight (lbs.)</b>	15	17	48	52	125	125
<b>Safety Certification</b>	-----UL Listed-----					

## AIR SCRUBBERS

	ScrubIT675	ScrubIT1950
<b>Rent air scrubbers for a healthy and safe environment!</b>		
<b>Air Capacity CFM Hi/Low</b>	675/450	1950/1300
<b>Power Requirements</b>	115V	115V
<b>Amp Rating</b>	9	9.4
<b>Power Connection</b>	Flanged Inlet, NEMA 5-15 Plug	Flanged Inlet, NEMA 5-15 Plug
<b>Motor</b>	1HP, 2-Speed Switch	1HP, 2-Speed Switch
<b>Blower</b>	2000 Rated Centrifugal Squirrel Cage	2000 Rated Centrifugal Squirrel Cage
<b>Filters (in.): Pad Filter</b>	16 x 16 x 1/4	24 x 24 x 1/4
<b>Ring Filter</b>	16 x 16 x 1/2	24 x 24 x 1/2
<b>HEPA Filter</b>	16 x 16 x 6	24 x 24 x 12
<b>Cabinet Dimensions w x d x h (in.)</b>	18 x 31 x 18	26 x 33 x 26
<b>Weight (lbs.)</b>	80	131
<b>Cabinet Style</b>	Aircraft Grade Aluminum	Aircraft Grade Aluminum
<b>Casters</b>	Heavy Duty, 2 Swivel, 2 Rigid	Heavy Duty, 2 Swivel, 2 Rigid
<b>Handles</b>	2 Handles on Top of Unit	4 Handles, 2 on each side
<b>Safety Certification</b>	UL Listed	UL Listed


## THE AIRPAC ADVANTAGE:

**Fast, friendly service**  
**Dependable, clean equipment**


## ACCESSORIES AND OTHER EQUIPMENT

- Flexible Duct
- Condensate pumps: 110V or 208V for high volume
- Power Distribution: Conductors (Cables), adapters
- Thermostats: 24V Wired or wireless
- Electric Heaters
- Flatbed Trailers
- Power Distribution Units (PDU)
- Diesel Generators

## DEHUMIDIFIERS

	DeHuIT250
<b>Rent dehumidifiers to maintain and restore proper humidity levels!</b>	
<b>Air Capacity CFM Hi/Low</b>	500/430
<b>Power Requirements</b>	115V
<b>Amp Rating</b>	9
<b>NEMA Plug/Cord Length</b>	LCDI 5-15P / 10'
<b>Pints/Day Dehumidification</b>	up to 250
<b>AHAM Rated Capacity@ 80F, 60% RH</b>	130 Pints
<b>Air Outlet Diameter (in.)</b>	8
<b>Drainage Hose length/Pump</b>	27' with 10' Vertical Lift
<b>Area of Coverage</b>	2500 SF
<b>Minimum/Maximum Temperature</b>	41°F / 95°F
<b>Filter</b>	Washable
<b>Cabinet Dimensions w x d x h (in.)</b>	23 x 21 x 38
<b>Weight (lbs.)</b>	121
<b>Controls</b>	Digital Electronic
<b>Decibel Rating</b>	60
<b>Refrigeration</b>	Low Grain
<b>Safety Certification</b>	ETL

## MOVING AIR

	FANIT2430
<b>Rent air movers to circulate air and ventilate spaces!</b>	
<b>Power Requirements</b>	115V
<b>Amp Rating</b>	2.00/1.80
<b>CFM High/Low</b>	8575/ 6475
<b>Dimension (w x d x h) (in.)</b>	30 x 13-1/4 x 30-1/2
<b>Weight (lbs.)</b>	41
<b>Description</b>	360° Fan Rotation
<b>Construction</b>	Metal
<b>Finish</b>	Powder Coated
<b>Power Cord Length (ft.)</b>	18
<b>Drive Type</b>	Direct Drive
<b>Fan Diameter (in.)</b>	24
<b>Mount Type</b>	Portable Swivel Base
<b>Decibel Rating</b>	65/57
<b>Safety Certification</b>	OSHA & UL Listed