

1 Identification

- **Product identifier**
- **Trade name: ResinWerks Vapor Barrier 100% Solids Moisture Control Epoxy Part A Clear**
- **Article number: 100-0000-A**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Resinwerks
7270 Gilpin Way Suite 100
Denver, CO 80229
USA
- **Information department: Product safety department**
- **Emergency telephone number: During normal opening times: +1 (720) 484-5160**

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

Trade name: ResinWerks Vapor Barrier 100% Solids Moisture Control Epoxy Part A Clear

(Contd. of page 1)

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**
oxirane, mono[(C12-14-alkyloxy)methyl] derivs
Stoddard solvent
- **Hazard statements**
Causes skin irritation.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
- **Precautionary statements**
If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 1
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = *1
Fire = 1
Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	>10-≤25%
------------	---	----------

(Contd. on page 3)

Printing date 11/08/2021

Reviewed on 08/27/2021

Trade name: ResinWerks Vapor Barrier 100% Solids Moisture Control Epoxy Part A Clear

(Contd. of page 2)

8052-41-3 Stoddard solvent

≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

8052-41-3	Stoddard solvent	300 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm

· **PAC-2:**

8052-41-3	Stoddard solvent	1,800 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm

· **PAC-3:**

8052-41-3	Stoddard solvent	29500** mg/m ³
-----------	------------------	---------------------------

(Contd. on page 4)

Trade name: ResinWerks Vapor Barrier 100% Solids Moisture Control Epoxy Part A Clear

(Contd. of page 3)

108-65-6 2-methoxy-1-methylethyl acetate

5000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Open and handle receptacle with care.
- **Information about protection against explosions and fires:**
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

8052-41-3 Stoddard solvent

PEL Long-term value: 2900 mg/m³, 500 ppm

REL Long-term value: 350 mg/m³
Ceiling limit value: 1800* mg/m³
*15-min

TLV Long-term value: 525 mg/m³, 100 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

US

Trade name: ResinWerks Vapor Barrier 100% Solids Moisture Control Epoxy Part A Clear

(Contd. of page 4)

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties**Information on basic physical and chemical properties****General Information****Appearance:****Form:**

Fluid

Color:

According to product specification

Odor:

Characteristic

Odor threshold:

Not determined.

pH-value:

Not applicable.

Change in condition**Melting point/Melting range:**

Undetermined.

Boiling point/Boiling range:

Undetermined.

Flash point:

> 100 °C (>212 °F)

Flammability (solid, gaseous):

Not determined.

Not applicable.

Decomposition temperature:

Not determined.

Auto igniting:

Product is not selfigniting.

Danger of explosion:

Product does not present an explosion hazard.

Explosion limits:**Lower:**

Not determined.

Upper:

Not determined.

Vapor pressure:

Not applicable.

Density at 20 °C (68 °F):1.13 g/cm³ (9.42985 lbs/gal)**Relative density**

Not determined.

Vapor density

Not applicable.

Evaporation rate

Not applicable.

Solubility in / Miscibility with**Water:**

Insoluble.

Partition coefficient (n-octanol/water): Not determined.**Viscosity:****Dynamic:**

Not applicable.

(Contd. on page 6)

Trade name: ResinWerks Vapor Barrier 100% Solids Moisture Control Epoxy Part A Clear

(Contd. of page 5)

Kinematic:	Not applicable.
Solvent content:	
Organic solvents:	0.0 %
VOC content:	0.01 % 0.0 g/l / 0.00 lb/gal
Solids content:	100.0 %
Other information:	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant
Carcinogenic.
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.

(Contd. on page 7)

Trade name: ResinWerks Vapor Barrier 100% Solids Moisture Control Epoxy Part A Clear

(Contd. of page 6)

- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|-----------------|
| · UN-Number | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · DOT, ADN, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · DOT, ADN, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · DOT, IMDG, IATA | not regulated |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | not regulated |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**
None of the ingredients is listed.
- **Section 313 (Specific toxic chemical listings):**
None of the ingredients is listed.

(Contd. on page 8)

Trade name: ResinWerks Vapor Barrier 100% Solids Moisture Control Epoxy Part A Clear

(Contd. of page 7)

· TSCA (Toxic Substances Control Act):

9003-36-5	formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs
68457-74-9	phenol, isobutylated, methylstyrenated
8052-41-3	Stoddard solvent
624-41-9	2-methylbutyl acetat
108-65-6	2-methoxy-1-methylethyl acetate

· Proposition 65**· Chemicals known to cause cancer:**

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories**· EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms

GHS07 GHS08

· Signal word Danger**· Hazard-determining components of labeling:**oxirane, mono[(C12-14-alkyloxy)methyl] derivs
Stoddard solvent**· Hazard statements**Causes skin irritation.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.**· Precautionary statements**If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 9)

Trade name: ResinWerks Vapor Barrier 100% Solids Moisture Control Epoxy Part A Clear

(Contd. of page 8)

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Ryan Fretz

· **Date of preparation / last revision** 11/08/2021 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B