



1 Identification

- **Product identifier**
- **Trade name: Resinwerks Epoxy Mortar Resurfacer Part B**
- **Article number: 150-5000-B**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Resinwerks, LLC
7270 Gilpin Way Suite 100
Denver, CO 80229 USA
- **Information department: Product safety department**
- **Emergency telephone number: (720) 484-5160**

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Repr. 1A H360 May damage fertility or the unborn child.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: Resinwerks Epoxy Mortar Resurfacer Part B

(Contd. of page 1)

· Hazard pictograms

GHS05 GHS07 GHS08

· Signal word *Danger***· Hazard-determining components of labeling:***2,2'-iminodiethylamine**bisphenol A**3,6,9-triazaundecamethylenediamine***· Hazard statements***Causes severe skin burns and eye damage.**May cause an allergic skin reaction.**May damage fertility or the unborn child.***· Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Do not breathe dusts or mists.**Wash thoroughly after handling.**Contaminated work clothing must not be allowed out of the workplace.**Wear protective gloves/protective clothing/eye protection/face protection.**If swallowed: Rinse mouth. Do NOT induce vomiting.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**Immediately call a poison center/doctor.**IF exposed or concerned: Get medical advice/attention.**Specific treatment (see on this label).**If skin irritation or rash occurs: Get medical advice/attention.**Wash contaminated clothing before reuse.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· Classification system:****· NFPA ratings (scale 0 - 4)**

Health = 3

Fire = 1

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

Health = *3

Fire = 1

Reactivity = 0

· Other hazards**· Results of PBT and vPvB assessment****· PBT:** *Not applicable.***· vPvB:** *Not applicable.*

US

(Contd. on page 3)

Trade name: Resinwerks Epoxy Mortar Resurfacer Part B

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

100-51-6	Benzyl alcohol	>25-≤50%
111-40-0	2,2'-iminodiethylamine	>2.5-≤10%
80-05-7	bisphenol A	>2.5-≤10%
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	>2.5-≤10%
112-57-2	3,6,9-triazaundecamethylenediamine	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

100-51-6	Benzyl alcohol	30 ppm
----------	----------------	--------

(Contd. on page 4)

Trade name: Resinwerks Epoxy Mortar Resurfacer Part B

(Contd. of page 3)

111-40-0	2,2'-iminodiethylamine	3 ppm
80-05-7	bisphenol A	15 mg/m ³
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	6.5 mg/m ³
112-57-2	3,6,9-triazaundecamethylenediamine	15 mg/m ³

· PAC-2:

100-51-6	Benzyl alcohol	52 ppm
111-40-0	2,2'-iminodiethylamine	8.5 ppm
80-05-7	bisphenol A	110 mg/m ³
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	72 mg/m ³
112-57-2	3,6,9-triazaundecamethylenediamine	130 mg/m ³

· PAC-3:

100-51-6	Benzyl alcohol	740 ppm
111-40-0	2,2'-iminodiethylamine	51 ppm
80-05-7	bisphenol A	650 mg/m ³
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	430 mg/m ³
112-57-2	3,6,9-triazaundecamethylenediamine	790 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Thorough dedusting.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

100-51-6 Benzyl alcohol	
WEEL	Long-term value: 10 ppm
111-40-0 2,2'-iminodiethylamine	
REL	Long-term value: 4 mg/m ³ , 1 ppm Skin
TLV	Long-term value: 4.2 mg/m ³ , 1 ppm Skin

(Contd. on page 5)

Trade name: Resinwerks Epoxy Mortar Resurfacer Part B

(Contd. of page 4)

112-57-2 3,6,9-triazaundecamethylenediamine

WEEL	Long-term value: 5 mg/m ³ Skin; DSEN
------	--

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Liquid
Color:	Colorless
Odor:	Characteristic
Odor threshold:	Not determined.

pH-value:	Not applicable.
------------------	-----------------

· **Change in condition**

Melting point/Melting range:	Undetermined.
-------------------------------------	---------------

(Contd. on page 6)

Trade name: Resinwerks Epoxy Mortar Resurfacer Part B

(Contd. of page 5)

Boiling point/Boiling range:	205.4 °C (401.7 °F)
· Flash point:	> 60 °C (>140 °F)
· Flammability (solid, gaseous):	Not determined. Not applicable.
· Ignition temperature:	325 °C (617 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	1.3 Vol %
Upper:	13 Vol %
· Vapor pressure at 20 °C (68 °F):	0.1 hPa (0.1 mm Hg)
· Density at 20 °C (68 °F):	1 g/cm ³ (8.345 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
· Solvent content:	
VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
Solids content:	100.0 %
· Other information:	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

100-51-6 Benzyl alcohol

Oral	LD50	1,230 mg/kg (rat)
------	------	-------------------

(Contd. on page 7)

Trade name: Resinwerks Epoxy Mortar Resurfacer Part B

(Contd. of page 6)

Dermal	LD50	2,000 mg/kg (rabbit)
111-40-0 2,2'-iminodiethylamine		
Oral	LD50	1,080 mg/kg (rat)
Dermal	LD50	1,090 mg/kg (rabbit)
80-05-7 bisphenol A		
Oral	LD50	3,250 mg/kg (rat)
Dermal	LD50	3,000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.



(Contd. on page 8)

Trade name: Resinwerks Epoxy Mortar Resurfacer Part B

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT, IMDG, IATA	UN1760
· UN proper shipping name · DOT · IMDG, IATA	Corrosive liquids, n.o.s. (Diethylenetriamine) CORROSIVE LIQUID, N.O.S. (DIETHYLENETRIAMINE)
· Transport hazard class(es) · DOT	
	
· Class · Label	8 Corrosive substances 8
· IMDG, IATA	
	
· Class · Label	8 Corrosive substances 8
· Packing group · DOT, IMDG, IATA	III
· Environmental hazards:	Not applicable.
· Special precautions for user · Danger code (Kemler): · EMS Number: · Segregation groups · Stowage Category · Stowage Code	Warning: Corrosive substances 80 F-A, S-B Alkalis A SW2 Clear of living quarters.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations	On passenger aircraft/rail: 25 kg On cargo aircraft only: 100 kg
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5 kg Code: E1 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

(Contd. on page 9)

Trade name: Resinwerks Epoxy Mortar Resurfacer Part B

(Contd. of page 8)

· **UN "Model Regulation":** UN 1760 CORROSIVE LIQUID, N.O.S.
(DIETHYLENETRIAMINE), 8, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

80-05-7 bisphenol A

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

80-05-7 bisphenol A

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

2,2'-iminodiethylamine

bisphenol A

3,6,9-triazaundecamethylenediamine

- **Hazard statements**

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

(Contd. on page 10)

Trade name: Resinwerks Epoxy Mortar Resurfacer Part B

(Contd. of page 9)

Precautionary statements*If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Do not breathe dusts or mists.**Wash thoroughly after handling.**Contaminated work clothing must not be allowed out of the workplace.**Wear protective gloves/protective clothing/eye protection/face protection.**If swallowed: Rinse mouth. Do NOT induce vomiting.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**Immediately call a poison center/doctor.**IF exposed or concerned: Get medical advice/attention.**Specific treatment (see on this label).**If skin irritation or rash occurs: Get medical advice/attention.**Wash contaminated clothing before reuse.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department issuing SDS: Environment protection department.**Contact:** Mr. Williams**Date of preparation / last revision** 09/02/2021 / -**Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Repr. 1A: Reproductive toxicity – Category 1A