

Page 1/10

Safety Data Sheet acc. to OSHA HCS

Reviewed on 06/16/2021

# 1 Identification

Printing date 07/12/2021

· Product identifier

· Trade name: Resinwerks WBE 500 Cloud Grey Part B

· Article number: 160-B102-B

· Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Resinwerks, LLC

7270 Gilpin Way Suite 100 Denver, CO 80229 USA

- · Information department: Product safety department
- Emergency telephone number: (720) 484-5160

# 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 1A H360 May damage fertility or the unborn child.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS08

Signal word Danger

(Contd. on page 2)

Reviewed on 06/16/2021

## Trade name: Resinwerks WBE 500 Cloud Grey Part B

(Contd. of page 1)

### · Hazard-determining components of labeling:

titanium dioxide

2-methoxypropanol

2,2'-iminodiethylamine

3,6,9-triazaundecamethylenediamine

#### · Hazard statements

May cause an allergic skin reaction.

Suspected of causing cancer.

May damage fertility or the unborn child.

#### · Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

### · Classification system:

### · NFPA ratings (scale 0 - 4)



Health = 1 *Fire* = 1 Reactivity = 0

### · HMIS-ratings (scale 0 - 4)



Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

1	· Dangerous components:		
Ī	13463-67-7	titanium dioxide	>10-≤25%
Ī	107-98-2	1-methoxy-2-propanol	>2.5-≤10%
Ī	111-40-0	2,2'-iminodiethylamine	≤2.5%
Ī	112-57-2	3,6,9-triazaundecamethylenediamine	≤2.5%
- 1		(Ci	ontd on page 3)

Reviewed on 06/16/2021

Trade name: Resinwerks WBE 500 Cloud Grey Part B

(Contd. of page 2)
1589-47-5 | 2-methoxypropanol ≤2.5%

## 4 First-aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

13463-67-7	titanium dioxide	30 mg/m³
107-98-2	1-methoxy-2-propanol	100 ppm
21645-51-2	aluminium hydroxide	8.7 mg/m <sup>3</sup>
1344-28-1	aluminium oxide	15 mg/m³
111-40-0	2,2'-iminodiethylamine	3 ррт
111-76-2	2-butoxyethanol	60 ppm
112-57-2	3,6,9-triazaundecamethylenediamine	15 mg/m³
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
57-55-6	Propylene Glycol	30 mg/m³

- US

Reviewed on 06/16/2021

### Trade name: Resinwerks WBE 500 Cloud Grey Part B

		(Contd. of page
PAC-2:		
13463-67-7	titanium dioxide	330 mg/m³
107-98-2	1-methoxy-2-propanol	160 ppm
21645-51-2	aluminium hydroxide	73 mg/m³
1344-28-1	aluminium oxide	170 mg/m³
111-40-0	2,2'-iminodiethylamine	8.5 ppm
111-76-2	2-butoxyethanol	120 ppm
112-57-2	3,6,9-triazaundecamethylenediamine	130 mg/m³
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
57-55-6	Propylene Glycol	1,300 mg/m
PAC-3:		<u>'</u>
13463-67-7	titanium dioxide	2,000 mg/m
107-98-2	1-methoxy-2-propanol	660 ppm
21645-51-2	aluminium hydroxide	440 mg/m³
1344-28-1	aluminium oxide	990 mg/m³
111-40-0	2,2'-iminodiethylamine	51 ppm
111-76-2	2-butoxyethanol	700 ppm
112-57-2	3,6,9-triazaundecamethylenediamine	790 mg/m³
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
57-55-6	Propylene Glycol	7,900 mg/m

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

(Contd. on page 5)

Reviewed on 06/16/2021

Trade name: Resinwerks WBE 500 Cloud Grey Part B

	(Contd. of page				
107-98	107-98-2 1-methoxy-2-propanol				
REL	Short-term value: 540 mg/m³, 150 ppm Long-term value: 360 mg/m³, 100 ppm				
TLV	Short-term value: 369 mg/m³, 100 ppm Long-term value: 184 mg/m³, 50 ppm				
111-40	0-0 2,2'-iminodiethylamine				
REL	Long-term value: 4 mg/m³, 1 ppm Skin				
TLV	Long-term value: 4.2 mg/m³, 1 ppm Skin				
112-57	112-57-2 3,6,9-triazaundecamethylenediamine				
WEEL	Long-term value: 5 mg/m³ Skin; DSEN				

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Breathing equipment: Not required.
- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Color: Different according to coloring

· Odor: Characteristic · Odor threshold: Not determined.

· pH-value: Not determined.

(Contd. on page 6)

Reviewed on 06/16/2021

# Trade name: Resinwerks WBE 500 Cloud Grey Part B

	(Contd. of pag
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
Flash point:	23 - 60 °C (73.4-140 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	270 °C (518 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
Density at 20 °C (68 °F):	1.295 g/cm³ (10.80678 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Miscible
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	7.0 %
Water:	34.6 %
VOC content:	6.97 %
	90.3 g/l / 0.75 lb/gal
Solids content:	26.6 %
Other infomation:	No further relevant information available.

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
- Thermal decomposition / conditions to be avoided:

- No decomposition if used according to specifications.

  Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Reviewed on 06/16/2021

Trade name: Resinwerks WBE 500 Cloud Grey Part B

(Contd. of page 6)

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:
- · Carcinogenic categories

IARC (Inter	national Agency for Research on Cancer)	
13463-67-7	titanium dioxide	2E
14807-96-6	Talc (Mg3H2(SiO3)4)	3
111-76-2	2-butoxyethanol	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	21
NTP (Nation	nal Toxicology Program)	
None of the	ingredients is listed.	
OSHA-Ca (	Occupational Safety & Health Administration)	
None of the	ingredients is listed.	

# 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Reviewed on 06/16/2021

Trade name: Resinwerks WBE 500 Cloud Grey Part B

(Contd. of page 7)

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · DOT, ADN, IMDG, IATA	not regulated
· UN proper shipping name · DOT, ADN, IMDG, IATA	not regulated
· Transport hazard class(es)	
· DOT, ADN, IMDG, IATA · Class	not regulated
· Packing group · DOT, IMDG, IATA	not regulated
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Stowage Category	Not applicable. B
· Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· UN "Model Regulation":	not regulated

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture · Sara

· Section 35	· Section 355 (extremely hazardous substances):		
None of the	None of the ingredients is listed.		
· Section 31	Section 313 (Specific toxic chemical listings):		
1344-28-1	aluminium oxide		
	2-butoxyethanol		
1330-20-7			
100-41-4	ethylbenzene		
· TSCA (To)	· TSCA (Toxic Substances Control Act):		
All ingredie	All ingredients are listed.		

· Proposition 65

· Chemicals known to cause cancer:	
13463-67-7	titanium dioxide
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 9)

Reviewed on 06/16/2021

### Trade name: Resinwerks WBE 500 Cloud Grey Part B

(Contd. of page 8)

## · Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

### · Carcinogenic categories

· EPA (Env	· EPA (Environmental Protection Agency)		
111-76-2	2-butoxyethanol	NL	
1330-20-7	xylene	1	
100-41-4	ethylbenzene	D	
· TLV (Thre	· TLV (Threshold Limit Value established by ACGIH)		
13463-67	7 titanium dioxide	A4	
14907.06	6 Tolo (Ma2H2/SiO2) (1)	Λ 1	

· TLV (Threshold Limit Value established by ACGIH)		
	titanium dioxide	A4
14807-96-6	Talc (Mg3H2(SiO3)4)	A4
1344-28-1	aluminium oxide	A4
	2-butoxyethanol	A3
1330-20-7		A4
100-41-4	ethylbenzene	A3

## · NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7 titanium dioxide

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

### · Hazard pictograms





· Signal word Danger

# · Hazard-determining components of labeling:

titanium dioxide

2-methoxypropanol

2,2'-iminodiethylamine

3,6,9-triazaundecamethylenediamine

### · Hazard statements

May cause an allergic skin reaction.

Suspected of causing cancer.

May damage fertility or the unborn child.

## Precautionary statements

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

(Contd. on page 10)

Reviewed on 06/16/2021

Trade name: Resinwerks WBE 500 Cloud Grey Part B

(Contd. of page 9)

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact: Mr. Williams

· Date of preparation / last revision 07/12/2021 / -

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2 Repr. 1A: Reproductive toxicity - Category 1A