

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 17, 2020 Revision: January 7, 2020

1 Identification

· Product identifier

· Trade name: Resinwerks Kinetic Patch Part A

· Other means of identification: No other identifiers

· Recommended use and restriction on use

Recommended use: Concrete repairs / Floor repairs
 Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

Resinwerks, LLC 7270 Gilpin Way #100 Denver, CO 80229 Phone: (720) 484-5160 Email: info@resinwerks.com

· Emergency telephone number:

ChemTel Inc.

(800) 255-3924 (North America) (801) 1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





GHS07 GHS08

· Signal word: Danger

· Hazard statements:

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Cont'd. on page 2)

Page: 2/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 17, 2020 Revision: January 7, 2020

Trade name: Resinwerks Kinetic Patch Part A

(Cont'd. of page 1)

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist/vapors/spray. P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection.
P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards

0 % of the mixture consists of component(s) of unknown toxicity.

There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:				
101-68-8 4,4'-methylenediphenyl diisocyanate				
Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335				
5873-54-1 o-(p-isocyanatobenzyl)phenyl isocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	10-30%			

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

Page: 3/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 17, 2020 Revision: January 7, 2020

Trade name: Resinwerks Kinetic Patch Part A

(Cont'd. of page 2)

4 First-aid measures

Description of first aid measures

After inhalation:

Supply fresh air and to be sure to call for a doctor.

Provide oxygen treatment if affected person has difficulty breathing.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Do not pull solidified product away from the skin.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Asthma attacks

Headache

Breathing difficulty

Dizziness

Coughing

Allergic reactions

Irritant to skin and mucous membranes.

Causes eve irritation.

Gastric or intestinal disorders when ingested.

Nausea in case of ingestion.

Vomiting.

Diarrhea.

Disorientation

· Danger:

Harmful if inhaled.

Danger of impaired breathing.

Danger of disturbed cardiac rhythm.

Danger of convulsion.

May cause respiratory irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause damage to organs through prolonged or repeated exposure.

Suspected of causing cancer.

· Indication of any immediate medical attention and special treatment needed:

Medical supervision for at least 48 hours.

Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

Contains 4,4'-methylenediphenyl diisocyanate, o-(p-isocyanatobenzyl)phenyl isocyanate. May produce an allergic reaction.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

In cases of irritation to the lungs, initial treatment with cortical steroid inhalants.

If medical advice is needed, have product container or label at hand.

Page: 4/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 17, 2020 Revision: January 7, 2020

Trade name: Resinwerks Kinetic Patch Part A

(Cont'd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

- For safety reasons unsuitable extinguishing agents: None.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol.

Ensure adequate ventilation.

Keep people at a distance and stay upwind.

- Environmental precautions Avoid release to the environment.
- Methods and material for containment and cleaning up

Allow to solidify. Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- ·Handling
- Precautions for safe handling:

Use only in well ventilated areas.

Avoid breathing mist, vapors, or spray.

Avoid contact with the eyes and skin.

Open and handle receptacle with care.

- Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Store in cool, dry conditions in well sealed receptacles.

· Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

· Specific end use(s) No relevant information available.

Page: 5/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 17, 2020 Revision: January 7, 2020

Trade name: Resinwerks Kinetic Patch Part A

(Cont'd. of page 4)

8 Exposure controls/personal protection

· Control parameters

Components with limit values that require monitoring at the workplace:				
101-68-8 4,4'-methylenediphenyl diisocyanate				
PEL (USA)	Ceiling limit value: 0.2 mg/m³, 0.02 ppm			
REL (USA)	Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min			
TLV (USA)	Long-term value: 0.051 mg/m³, 0.005 ppm			
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm Skin; S(R)			
EV (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.02 ppm			
LMPE (Mexico)	Long-term value: 0.005 ppm			
5873-54-1 o-(p-isocyanatobenzyl)phenyl isocyanate				
EL (Canada)	Long-term value: 0.005 ppm Ceiling limit value: 0.01 ppm S			

Exposure controls

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Be sure to clean skin thoroughly after work and before breaks.

- **Engineering controls:** Use only outdoors or in a well-ventilated area.
- · Breathing equipment:



Combined Organic Vapor and Particulate Respirator is recommended for use during all processing activities.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Eye protection:



Safety glasses

· Body protection: Protective work clothing

(Cont'd. on page 6)

Page: 6/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 17, 2020 Revision: January 7, 2020

Trade name: Resinwerks Kinetic Patch Part A

(Cont'd. of page 5)

· Limitation and supervision of exposure into the environment

Avoid release to the environment.

· Risk management measures No relevant information available.

9 Physical and chemical properties				
Information on basic physical and chemical properties				
· Appearance:				
Form:	Liquid			
Color:	According to product specification			
· Odor:	Not determined.			
Odor threshold:	Not determined.			
· pH-value:	Neutral			
· Melting point/Melting range:	Not determined.			
· Boiling point/Boiling range:	Not determined.			
· Flash point:	203 °C (397.4 °F)			
· Flammability (solid, gaseous):	Not applicable.			
· Auto-ignition temperature:	Not determined.			
Decomposition temperature:	Not determined.			
· Danger of explosion:	Product does not present an explosion hazard.			
· Explosion limits				
Lower:	Not determined.			
Upper:	Not determined.			
· Oxidizing properties:	Non-oxidizing.			
· Vapor pressure:	Not determined.			
· Density:				
Relative density:	1.23			
Vapor density:	Not determined.			
Evaporation rate:	Not determined.			
· Solubility in / Miscibility with				
Water:	Not miscible or difficult to mix.			
Partition coefficient (n-octanol/wa	ater): Not determined.			
· Viscosity				
Dynamic:	Not determined.			
Kinematic at 25 °C (77 °F):	65-115 cP			
Other information	No relevant information available.			

10 Stability and reactivity

· Reactivity: No relevant information available.

(Cont'd. on page 7)

Page: 7/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 17, 2020 Revision: January 7, 2020

Trade name: Resinwerks Kinetic Patch Part A

(Cont'd. of page 6)

- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Reacts with oxidizing agents.

Reacts with strong acids and alkali.

Contact with acids releases toxic gases.

· Conditions to avoid

Excessive heat.

Avoid acids.

- · Incompatible materials Oxidizers, strong bases, strong acids
- · Hazardous decomposition products

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Hydrogen cyanide (prussic acid)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Harmful if inhaled.
- LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

- · Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Causes eye irritation.
- · Sensitization:

Contains 4,4'-methylenediphenyl diisocyanate, o-(p-isocyanatobenzyl)phenyl isocyanate. May produce an allergic reaction.

May cause sensitisation by inhalation and skin contact.

IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Suspected of causing cancer.
- Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: May cause respiratory irritation.
- **STOT-repeated exposure:** May cause damage to organs through prolonged or repeated exposure.

(Cont'd. on page 8)

Page: 8/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 17, 2020 Revision: January 7, 2020

Trade name: Resinwerks Kinetic Patch Part A

(Cont'd. of page 7)

· Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- ·Toxicity
- Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · **Mobility in soil:** No relevant information available.
- Additional ecological information
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
· UN proper shipping name · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
· Transport hazard class(es)		
· DOT, ADR/RID/ADN, IMDG, IATA · Class	Not regulated.	
· Packing group · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
· Environmental hazards		
		(Cont'd. on page 9)

Page: 9/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 17, 2020 Revision: January 7, 2020

Trade name: Resinwerks Kinetic Patch Part A

(Cont'd. of page 8)

• Marine pollutant:

• Special precautions for user

• Not applicable.

• Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

• Not applicable.

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

Section 313 (Specific toxic chemical listings):

101-68-8 4,4'-methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

EPA (Environmental Protection Agency):

101-68-8 4,4'-methylenediphenyl diisocyanate

D, CBD

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL) (Substances not listed.):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Cont'd. on page 10)

Page: 10/10

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: January 17, 2020 Revision: January 7, 2020

Trade name: Resinwerks Kinetic Patch Part A

(Cont'd. of page 9)

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health Administration

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com