MATERIAL SAFETY DATA SHEET

Product: Polyethylene

Review: 4

Date: 02/06/2005

Page: 1 /8

MSDS

1. Product and Company Identification

Product Name	Polyethylene
Internal Identification code of the product	LDPE, MDPE, MLDPE, LLDPE, HDPE
	Braskem S.A.
Address	Braskem S.A Unidade Triunfo BR 386 - Rodovia Tabaí canoas, Km 419 s/n° Via Contorno 1216 - Polo Petroquímico - Triunfo Rio Grande do Sul - Phone: (0xx51) 457-5400 Fax: (0xx51) 457-1336
	Braskem S.A Unidade Polietileno Camaçari Rua Eteno, 1582 Pólo Petroquímico - Copec 42810-000 Camaçari - BA Brasil Tel. (0XX71) 3634-3700 Fax (0XX71) 3634-3797 / 3811 / 3819
	Braskem – Polialden Petroquímica S.A. Rua Hidrogênio, 3520 Pólo Petroquímico - Copec 42810-000 Camaçari - BA Brasil Tel. (0XX71) 3632-6460 Fax (0XX71) 3632-1266
	Braskem S.A. – Commercial Office Av. das Nações Unidas, 4777 05477-000 - São Paulo - SP Phone: (11) 3443-9000 Fax: (11) 3023-0415
Company Phone	(11) 3443-9000
Emergency Number	(51) 457-5400
Fax	(51) 457-1084

2. COMPOSITION / INFORMATION ON INGREDIENTS

Substância:	Polyethylene Resin
Chemical Name	Low Density Polyethylene, Linear Low Density Polyethylene, Medium Density Polyethylene, Medium Linear Density Polyethylene, High Density Polyethylene
Synonym	LDPE, MDPE, MLDPE, LLDPE, HDPE
CAS Number	009002-88-4 (homopolymer) ;
	25087-34-7 (ethylene -1- butene copolymer)
	25213-02-9 (ethylene –1- hexene copolymer)
Ingredients that contribute to hazard	Not applicable. Inert substance.

MSDS

MATERIAL SAFETY DATA SHEET

Product: Polyethylene

Review: 4

Date: 02/06/2005

Page: 2 /8

3. HAZARDS IDENTIFICATION

Important hazarduos effects	Stable product. It doesn't offer hazard in its normal handling and storage state
Product effects	The product is harmless to human contact and non-biodegradable. It can be reused in case of loss if not contaminated by any other external agent. It does not present specific hazard.
Health effects	The product does not offer risks in its normal state. It should not be swallowed. Combustion and decomposition may produce hazardous fumes. Avoid breathing dust or vapor. Hot or molten material can cause thermal burns if in contact to the skin. In powder form, may cause mechanical irritation if in contact to the eyes.
Environmental effects	Non-biodegradable product. It can be packed and reused if necessary.
 Physical and Chemical Hazards 	No risks to operators have been reported when handling the product in room temperature conditions. Protection equipment is not required during handling due to the non-chemical reactivity characteristics of the product
	When in direct combustion, it generates flames, produces water, carbon dioxide and in lack of oxygen it also generates carbon monoxide. The products from fire are irritant and toxic. High combustion temperatures (from 400°C to 700°C) can form other products such as; aldehydes and hydrocarbonates.
	Fine powder may become a dust explosion hazard if suspended in air.
Specific Hazards	NA – Inert Substance.
Chemical Product Classification	Product not classified as hazardous by UNO
Emergency Overview	The product is not flammable in normal conditions, but it may ignite when in direct contact with flames. In case of fire, evacuate all personnel from affected area and follow the procedures of item 4 – First Aid Section

MSDS

MATERIAL SAFETY DATA SHEET

Product: Polyethylene

Review: 4

Date: 02/06/2005

Page: 3 /8

4. EMERGENCY AND FIRST AID PROCEDURES

First Aid Procedures:

Inhalation:	The material is not expected to present inhalation hazard in normal temperature conditions. Overheating can produce fumes such as; propene and ethene monomers, low molecular weight polymers and their products of oxidation. Very low levels of other products such as, aldehydes and acids may be generated. At processing, natural ventilation or local exhaust are recommended in the working area.
Skin Contact	Risks not known when the material is in room temperature conditions. Contact with overheated material will cause thermal burns.
Eyes Contact	Health hazards are not known. Mechanical irritation may be caused. In this case, immediately flush eyes with water (abundantly). Safety glasses are recommended in the working area.
Ingestion	Chemical products should not be ingested. No adverse health effects are expected from ingestion of polyethylene resins. However, it may cause throat obstruction when swallowed. In case of accidental occurrence, get medical attention.

5. FIRE FIGHTING MEASURES

Appropriate extinguishing media	In case of fire, evacuate all personnel from affected areas. Observe fumes from burning material. In combustion, Polyethylene produces class A fire which should be extinguished with water spray, foam, dry chemical or Carbon Dioxide (CO_2).
Fire Fighters Protection	Fire fighters and others exposed to products of combustion should wear full protective clothing including Self-Contained Breathing Apparatus (SCBA). Personnel without this protection should evacuate the area to prevent exposition to fumes. In confined or non-ventilated areas SCBA should also be used for cleaning the area after fire fighting.

MSDS

MATERIAL SAFETY DATA SHEET

Product: Polyethylene

Review: 4

Date: 02/06/2005

Page: 4 /8

6. ACCIDENTAL RELEASE MEASURES.

Personal Precautions

- Sources of Ignition Sources of ignition should be removed from contact with resin provenient from spilling or release.
- Dust Control Polyethylene is commercialized as pellets. The use of masks is not necessary. However, when consumed in dust form, protecting masks approved by MTE (Brazilian work and employment organization) should be used.
- Exposure Controls Already described in item 4 First Aid Mesures. (inhalation, skin, eyes and mucus):

Environment Protection If possible, stop leaking. Keep the product away from public sewer system and waterways.

Clean up by vacuuming or wet sweeping for reusing or disposal.

• Waste Disposal Landfill or incineration in compliance with federal, state and local regulations. According to NBR – 10004 (solid remains classification by ABNT) polyethylene resins are not considered hazardous for disposal. When incinerated attention to gas produced.

7 HANDLING AND STORAGE

Handling:

- Technical Measures:
 - Prevention of Personal Exposition
 Natural ventilation is required and respiratory protection is not necessary if pellets are being handled. If the product is in its powder form, avoid inhalation of the dust generated by the powder. Inspect handling system regularly for possible accumulation of dust. Eating or drinking is the areas where the product is handled should be avoided.
 - Prevention of Fire and Explosions: The product is not flammable but it may ignite when in contact with flames.
 - Safe Handling:
 Protective gloves are required when handling hot material during product processing. Safety glasses are recommended in all working areas. Do not smoke where polymer dust is present.

MSDS

MATERIAL SAFETY DATA SHEET

Product: Polyethylene

Review: 4	Date: 02/06/2005	Page: 5 /8
Safe Handling Orientation:	Not Applicable. The products is inert and incompatibility with other products.	l it doesn't present
Storage:	Maximum storage period: 15 months	
Appropriate Technical Measures:	Not Applicable	
Storage Conditions	The products should be stored in cool, well-ve from sun rays.	entilated area away
Adequate:	It is recommended the storage of 55 sacks of bench (1.375 tons) in pallets with appropriate The limit of two pilled up pallets should be ob	e devices for moving.
 Incompatible Materials and Products: 	Store away from concentrated acids, chlorina aromatic compounds.	ted solvents and
Safe Package Materials:		
Recommended:	Polyethylene resin is an inert material and ca polyethylene bags	n be packed in

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Appropriate Individual Protection:

Respiratory Protection:	None under normal processing if ventilation is adequate. If in powder form, approved half-face respirator is recommended.
Eyes Protection:	Safety glasses are recommended in any work area.
Skin and Body Protection:	Gloves are required when handling hot polymer.
Hygiene Measures:	Eating and drinking should be avoided in the areas where the product is being handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid
Appearance:	Pellets shape or powder
Color :	Translucid or white
Odour :	Odourless or candle-like smell
pH :	Not Applicable
Specific tempeartures that may change the product physical state.	Melting Point 90°C – 120°C
Fulgurating Point	Not applicable

MATERIAL SAFETY DATA SHEET

Product: Polyethylene

Review: 4	Date: 02/06/2005	Page: 6 /8
Ignition Point:	350°C	
Explosion Limits:	Not available	
Density:	0,913 – 0,964 g/cm ³	
Solubility in water:	Insoluble	
Solubility in other solvents:	Xylene	

10 STABILITY AND REACTIVITY

Specific conditions:	
 Instability: 	Polyethylene resins are stable. Depolymerization not observed.
Hazardous Reactions:	Not Applicable
Incompatible Materials or Substances:	Degradation of Polyethylene may result from the contact with certain chemical products such as; concentrated acids, chlorinated solvents or aromatic compounds. Changes in molecular structure may occur if the product is overheated, exposed to radiation like in long sun light exposition.
Hazardous Products from Decomposition:	The products that result from polyethylene resins combustion should be considered toxic.Carbon Monoxide, which is asphyxiating, may be produced.

11. TOXICOLOGICAL INFORMATION

Information according to different exposition media: Polyethylene does not appear to possess any toxicological properties. Carcinogenic, mutagenic, teratogenic, embriotoxic, toxic ar any other specific effects are not known.

MSDS

MATERIAL SAFETY DATA SHEET

Product: Polyethylene

Review: 4

Date: 02/06/2005

Page: 7 /8

12. ECOLOGICAL INFORMATION

Environmental Effects:

Non polutant and non biodegradable product. Effects on nature due to bioaccumulation are not known.

13. DISPOSAL CONSIDERATIONS

Disposal Methods:

Product : Waste disposal in landfills or incineration in compliance with federal, state and local regulations. For waste disposal, polyethylene resins are not classified as hazardous according to NBR-10004 (ABNT). Dispose in accordance to federal, state and local laws. When incinerated observe gas generation.
 Product Remains: Follow the same treatment of waste disposal methods.
 Package to be used: Polyethylene bags should be reused in the working area, products transportation or recycled by specialized companies. Big Bag packages should be returned to Braskem.

14. TRANSPORT INFORMATION

National and International Regulations:For domestic transportation, polyethylene resins are not classified as
hazardous by Brazilian Transportation Organization. According to UNO
resolutions and to "Regulamentação do Transporte Rodoviário de
Produtos Perigosos" (Regulation for Road Transportation of Hazardous
Products), approved by law nº 96044/88, polyethylene is not considered
hazardous.Special Precaution Measures for Transportation: Loading should be
protected to avoid humidity and product leaking.Please consult the regulations of the importing country.

MSDS

MATERIAL SAFETY DATA SHEET

Product: Polyethylene

Review: 4

Date: 02/06/2005

Page: 8 /8

15. REGULATORY INFORMATION

Regulations:

There are no specific regulations applicable to polyethylene resins. All the ingredients of this product comply with TCSA Inventory Regulations.

16. OTHER INFORMATION

Complementary Information:	Risk Codes:
	– NFPA (1)
	– HMIS (2)
	– Health Risk 0
	 Flammability Risk 1
	 Reactivity Risk 0
Information Source:	National Fire Protection Association (USA)
	Hazardous Materials Identification System, National Paint and Coatings Association (USA)