




FloodLUX COMPACT 50


Art.Nr.: 455012050008
EAN: 4260374012764



LIGHT DISTRIBUTION CURVE



TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	120°
color temperature	5.000 K
color tolerance	< 5 SDCM
color rendering index	> 70

PROPERTIES

through-wiring	No
connection	Cable: 3 x 1,0 mm ² , 0,5 m
power factor	> 0.95
module per circuit breaker B10A	41
module per circuit breaker B16A	66
module per circuit breaker C10A	41
module per circuit breaker C16A	66
switching cycles	> 200.000
voltage range AC	220 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

FloodLUX COMPACT 50	
product code	455012050008
EAN code	4260374012764
warranty	2 years

ACCESSORIES

No accessories available

PERFORMANCE

luminous efficiency	90 lm/W
system performance	50 W
luminous flux	4.500 lm
dimnable	No

RESILIENCE

protection class	I
impact resistance	IK05
protection type	IP65
lifespan	> 40.000 h [L70, B10]
UV resistant	Yes
operating temperature	-20 to +45 °C
foodready	No

MATERIAL

cover	Transparent cover
material (cover)	Glass
material (housing)	Aluminium
housing color	Black

SCOPE OF DELIVERY

no accessory included

DIMENSION

L x W x H / Ø (H2)	230 x 172 (193) x 32 (133) mm
weight	1,1 kg