




# FloodLUX PRO

80 | 50 x 125° | 5.000K


Art.Nr.: 455008000023  
EAN: 4260374017240



## LIGHT DISTRIBUTION CURVE



## TECHNICAL DRAWING



## LIGHT INFORMATION

beam angle	50 x 125°
color temperature	5.000 K
color tolerance	< 5 SDCM
color rendering index	> 80

## PROPERTIES

through-wiring	No
connection	Cable: 3 x 1,0 mm <sup>2</sup> , 1,3 m
power factor	> 0.90
module per circuit breaker B10A	4
module per circuit breaker B16A	6
module per circuit breaker C10A	6
module per circuit breaker C16A	10
switching cycles	> 500.000
voltage range AC	100 – 240 V AC, 50/60 Hz

## ORDER OVERVIEW

FloodLUX PRO 80   50 x 125°   5.000K	
product code	455008000023
EAN code	4260374017240
warranty	5 years

## ACCESSORIES

No accessories available
--------------------------

## PERFORMANCE

luminous efficiency	138 lm/W
system performance	80 W
luminous flux	11.000 lm
dimnable	No

## RESILIENCE

protection class	I
impact resistance	IK08
protection type	IP66
lifespan	> 60.000 h [L80, B10]
UV resistant	Yes
operating temperature	-30 to +45 °C
foodready	No

## MATERIAL

cover	Transparent cover
material (cover)	Glass
material (housing)	Aluminium
housing color	Black

## SCOPE OF DELIVERY

no accessory included
-----------------------

## DIMENSION

L x W x H / Ø (H2)	308 x 317 (360) x 83 (153) mm
weight	4,3 kg