





IndustryLUX FARO X3 800-75

Art.Nr.: 110850230021
EAN: 4260374014065



LIGHT DISTRIBUTION CURVE

TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	75°
color temperature	5.000 K
color tolerance	< 5 SDCM
color rendering index	> 83

PROPERTIES

through-wiring	5 x 1,5 mm ²
connection	Terminal: 5-pole max. 1,5 mm ²
power factor	> 0.95
module per circuit breaker B10A	37
module per circuit breaker B16A	60
module per circuit breaker C10A	63
module per circuit breaker C16A	101
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz
voltage range DC	176 - 276 V DC

ORDER OVERVIEW

IndustryLUX FARO X3 800-75	
product code	110850230021
EAN code	4260374014065
warranty	5 years

ACCESSORIES

Mounting plate for 2-3 luminaires
Cord suspension 2m
Top-Entry-Cap

PERFORMANCE

luminous efficiency	148 lm/W
system performance	23 W
luminous flux	3.400 lm
dimnable	Dip switch

RESILIENCE

protection class	II
impact resistance	IK08
protection type	IP65
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	-25 to +50 °C
foodready	Yes

MATERIAL

cover	diffuse cover
material (cover)	PC
material (housing)	PC
housing color	White

SCOPE OF DELIVERY

includes 2x mounting clip and cable gland M20

DIMENSION

L x W x H / Ø (H2)	800 x 104 x 57 (77) mm
weight	1,3 kg