




IndustryLUX
FARO X3
HTS 1500-140 DALI I 5.000 K

Art.Nr.: 111550650068
EAN: 4260374015758



LIGHT DISTRIBUTION CURVE

TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	140°
color temperature	5.000 K
color tolerance	< 5 SDCM
color rendering index	> 83

PROPERTIES

through-wiring	5 x 1,5 mm ²
connection	Terminal: 5-pole max. 1,5 mm ²
power factor	> 0.95
module per circuit breaker B10A	32
module per circuit breaker B16A	51
module per circuit breaker C10A	32
module per circuit breaker C16A	51
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

IndustryLUX FARO X3 HTS 1500-140
DALI I 5.000 K

product code	111550650068
EAN code	4260374015758
warranty	5 years

ACCESSORIES

Mounting plate for 2-3 luminaires
Cord suspension 2m
Top-Entry-Cap

PERFORMANCE

luminous efficiency	131 lm/W
system performance	65 W
luminous flux	8.500 lm
dimnable	DALI

RESILIENCE

protection class	II
impact resistance	IK08
protection type	IP65
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	-30 to +60 °C
foodready	Yes

MATERIAL

cover	diffuse cover
material (cover)	PC
material (housing)	PC
housing color	White

SCOPE OF DELIVERY

includes 2x mounting clip and cable gland M20

DIMENSION

L x W x H / Ø (H2)	1.500 x 104 x 57 (77) mm
weight	2,5 kg