





IndustryLUX
FLAT NEO
 156 | 60 x 60° | 4.000K

Art.Nr.: 44401560048
 EAN: 4260374018209



LIGHT DISTRIBUTION CURVE

TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	60 x 60°
color temperature	4.000 K
color tolerance	< 5 SDCM
color rendering index	< 80

PROPERTIES

through-wiring	No
connection	Plug: 3-pole max. 2,5 mm ²
power factor	> 0.95
module per circuit breaker B10A	2
module per circuit breaker B16A	4
module per circuit breaker C10A	4
module per circuit breaker C16A	7
switching cycles	> 500.000
voltage range AC	100 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

IndustryLUX FLAT NEO 156 | 60 x 60°
| 4.000K

product code	444015600048
EAN code	4260374018209
warranty	5 years

ACCESSORIES

No accessories available

PERFORMANCE

luminous efficiency	142 lm/W
system performance	156 W
luminous flux	22.100 lm
dimnable	No

RESILIENCE

protection class	I
impact resistance	IK10
protection type	IP65
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	-40 to +50 °C
foodready	No

MATERIAL

cover	Transparent cover
material (cover)	PC
material (housing)	Aluminium
housing color	Black

SCOPE OF DELIVERY

includes connector plug

DIMENSION

L x W x H / Ø (H2)	381 x 328 (399) x 58 (208) mm
weight	7,0 kg