





# IndustryLUX HEMERA 100-80

Art.Nr.: 43508010022  
EAN: 4260374013495



LIGHT DISTRIBUTION CURVE

TECHNICAL DRAWING



## LIGHT INFORMATION

beam angle	80°
color temperature	5.000 K
color tolerance	< 4 SDCM
color rendering index	> 83

## PROPERTIES

through-wiring	No
connection	Cable: 3 x 1,0 mm <sup>2</sup>   0,2 m
power factor	> 0.95
module per circuit breaker B10A	21
module per circuit breaker B16A	33
module per circuit breaker C10A	21
module per circuit breaker C16A	33
switching cycles	> 500.000
voltage range AC	100 – 240 V AC, 50/60 Hz

## ORDER OVERVIEW

IndustryLUX HEMERA 100-80	
product code	435080100022
EAN code	4260374013495
warranty	5 years

## ACCESSORIES

No accessories available
--------------------------

## PERFORMANCE

luminous efficiency	137 lm/W
system performance	100 W
luminous flux	13.700 lm
dimnable	No

## RESILIENCE

protection class	I
impact resistance	IK08
protection type	IP65
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	-30 to +55 °C
foodready	No

## MATERIAL

cover	Transparent cover
material (cover)	PC
material (housing)	Aluminium
housing color	Black

## SCOPE OF DELIVERY

no accessory included
-----------------------

## DIMENSION

L x W x H / Ø (H2)	Ø 400 x 138 (185) mm
weight	4,7 kg