

LIGHT INFORMATION

beam angle	80°
color temperature	5.000 K
color tolerance	< 4 SDCM
color rendering index	> 83

PROPERTIES

through-wiring	No
connection	Cable: 3 x 1,0 mm ² + 2 x 0,5 mm ² 0,2 m
power factor	> 0.95
module per circuit breaker B10A	13
module per circuit breaker B16A	21
module per circuit breaker C10A	13
module per circuit breaker C16A	21
switching cycles	> 500.000
voltage range AC	100 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

IndustryLUX HEMERA 160-80	
product code	435080960025
EAN code	4260374013525
warranty	5 years

ACCESSORIES

No accessories available

PERFORMANCE

luminous efficiency	141 lm/W
system performance	160 W
luminous flux	22.500 lm
dimnable	DALI

RESILIENCE

protection class	I
impact resistance	IK08
protection type	IP65
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	-30 to +55 °C
foodready	No

MATERIAL

cover	Transparent cover
material (cover)	PC
material (housing)	Aluminium
housing color	Black

SCOPE OF DELIVERY

no accessory included

DIMENSION

L x W x H / Ø (H2)	Ø 400 x 138 (185) mm
weight	5,1 kg