

INDUSTRYLUX HT



350

Art.Nr.: 435070350053
EAN: 4260374015833



LIGHT DISTRIBUTION CURVE

TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	80°
color temperature	5.000 K
color tolerance	< 5 SDCM
color rendering index	< 80

PROPERTIES

through-wiring	No
connection	Cable, 3 x 1,0 mm ² , 1,5 m
power factor	> 0.95
module per circuit breaker B10A	1
module per circuit breaker B16A	3
module per circuit breaker C10A	3
module per circuit breaker C16A	5
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

IndustryLUX HT 350	
product code	435070350053
EAN code	4260374015833
warranty	5 years

ACCESSORIES

PERFORMANCE

luminous efficiency	134 lm/W
system performance	350 W
luminous flux	47.000 lm
dimnable	No

RESILIENCE

protection class	I
impact resistance	IK06
protection type	IP65
lifespan	> 80.000 h [L80, B10]
UV resistant	Yes
operating temperature	-30 to +70 °C
foodready	No

MATERIAL

cover	Transparent cover
material (cover)	Glass
material (housing)	Aluminium
housing color	Grey

SCOPE OF DELIVERY

no accessory included

DIMENSION

L x W x H / Ø (H2)	Ø 610 (320) x 440 mm
weight	26,4 kg