





# IndustryLUX RODALIS ECO 145

Art.Nr.: 435012140046  
EAN: 4260374015598



LIGHT DISTRIBUTION CURVE

TECHNICAL DRAWING



## LIGHT INFORMATION

beam angle	120°
color temperature	5.000 K
color tolerance	< 5 SDCM
color rendering index	> 80

## PROPERTIES

through-wiring	No
connection	Cable: 3 x 1,0 mm <sup>2</sup> , 1,5 m
power factor	> 0.95
module per circuit breaker B10A	2
module per circuit breaker B16A	3
module per circuit breaker C10A	3
module per circuit breaker C16A	5
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz

## ORDER OVERVIEW

IndustryLUX RODALIS ECO 145	
product code	435012140046
EAN code	4260374015598
warranty	3 years

## ACCESSORIES

No accessories available
--------------------------

## PERFORMANCE

luminous efficiency	137 lm/W
system performance	145 W
luminous flux	19.800 lm
dimnable	No

## RESILIENCE

protection class	I
impact resistance	IK08
protection type	IP65
lifespan	> 50.000 h [L80, B10]
UV resistant	Yes
operating temperature	-30 to +45 °C
foodready	No

## MATERIAL

cover	Transparent cover
material (cover)	Glass
material (housing)	Aluminium
housing color	Black

## SCOPE OF DELIVERY

no accessory included
-----------------------

## DIMENSION

L x W x H / Ø (H2)	Ø 287 (144) x 76 (186) mm
weight	4,1 kg