





IndustryLUX RODALIS PRO 80

Art.Nr.: 435012080048
EAN: 4260374015611



LIGHT DISTRIBUTION CURVE

TECHNICAL DRAWING



LIGHT INFORMATION

beam angle	120°
color temperature	5.000 K
color tolerance	< 5 SDCM
color rendering index	> 80

PROPERTIES

through-wiring	No
connection	Cable: 3 x 1,0 mm ² , 1,5 m
power factor	> 0.95
module per circuit breaker B10A	3
module per circuit breaker B16A	5
module per circuit breaker C10A	6
module per circuit breaker C16A	9
switching cycles	> 500.000
voltage range AC	220 – 240 V AC, 50/60 Hz

ORDER OVERVIEW

IndustryLUX RODALIS PRO 80	
product code	435012080048
EAN code	4260374015611
warranty	5 years

ACCESSORIES

No accessories available

PERFORMANCE

luminous efficiency	194 lm/W
system performance	80 W
luminous flux	15.500 lm
dimnable	No

RESILIENCE

protection class	I
impact resistance	IK08
protection type	IP65
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	-30 to +50 °C
foodready	No

MATERIAL

cover	Transparent cover
material (cover)	PC
material (housing)	Aluminium
housing color	Black

SCOPE OF DELIVERY

no accessory included

DIMENSION

L x W x H / Ø (H2)	Ø 260 (130) x 62 (180) mm
weight	2,7 kg