



## LIGHT INFORMATION

beam angle	80°
color temperature	4.000 K
color tolerance	< 5 SDCM
color rendering index	> 80

## PROPERTIES

through-wiring	According to power supply
connection	According to power supply
power factor	> 0.95
module per circuit breaker B10A	52
module per circuit breaker B16A	83
module per circuit breaker C10A	52
module per circuit breaker C16A	83
switching cycles	> 500.000
voltage range AC	Je nach VSG

## ORDER OVERVIEW

PanelLUX SQUARE I 4.000 K	
product code	626240340021
EAN code	4260374019237
warranty	4 years

## ACCESSORIES

Cord suspension for PanelLUX SQUARE/LONG
Flush mounting frame for PanelLUX SQUARE

## PERFORMANCE

luminous efficiency	124 lm/W
system performance	34 W
luminous flux	4.200 lm
dimnable	According to power supply

## RESILIENCE

protection class	III
impact resistance	IK07
protection type	IP20
lifespan	> 50.000 h [L80, B10]
UV resistant	Limited
operating temperature	-25 to +45 °C
foodready	No

## MATERIAL

cover	Prismatic cover
material (cover)	PC
material (housing)	Aluminium
housing color	White

## SCOPE OF DELIVERY

several power supply options available (not included)
---

## DIMENSION

L x W x H / Ø (H2)	620 x 620 x 10 (46) mm
weight	2,7 kg