MEDIUM-DUTY CARRIER Steel Best-In-Class 7.5-Ton Carrier

Top Five Reasons To Make This Carrier Yours

1. Jerr-Dan's exclusive No-Lube[™] technology saves maintenance time

2. Loading and unloading angles are really low because this carrier has a full 11 feet of slide cylinder stroke. This gives you the flexibility to

3. An optional Zero-Degree Wheel Lift has the best clearance to recover

4. The weatherproof automotive style electrical system with

5. Get the look you want with removable steel or polished aluminum rails.

Packard connectors ensures that your carrier can stand up to any

a high performance composite.

even the lowest profile cars.

weather conditions.

handle mid-size loads as well as regular cars.

and costs. All major pivot points are greaseless and the slide pads are



Loading and unloading angles are extremely low because this carrier has a full 11 feet of slide cylinder stroke. This gives you the flexibility to handle mid-size loads as well as regular cars. An optional Zero-Degree Wheel Lift has the best clearance to recover even the lowest profile cars. The weatherproof automotive style electrical system with Packard connectors ensures that your carrier can stand up to any weather conditions. Get the look you want with removable steel or polished aluminum rails.

Specifications:

Deck Specifications

Capacity:
Winch Line Pull (first layer):
Length:
Width:
Deck Height (above top of frame rail):
Туре:
Denvired Dimensions Oak to Auto

15,000 lbs 10,000 lbs 22', 24', 26', 28' 96", 102" 11.19" Steel

Required Dimensions Cab to Axle

22':			
24':			
26':			
28':			

Recommended Minimum Chassis Requirements: GVWR: 25,500 lbs **Rear GVWR:** 17.500 lbs 1,500,000 in-lbs **RBM Total** (both rails combined): Frame Height for Optimal Load Angle 34"-39" Minimum Frame Length Behind Rear Axle 34"

FEATURES



. Nylon Cable Chain Hose and Wiring System

This ingenious system protects wiring and hydraulic hoses, and its L-shape stops water from pooling and freezing in winter.



2. Worm Gear Winch

Get 10,000 lbs capacity and 32 fpm with our Worm Gear Winch with Remote Free Spool.

3. ZOD Wheel Lift

The optional Zero-Degree Wheel Lift provides maximum clearance to towed vehicles regardless of ground profile.

or 28' of deck, plenty of best-in-class features, and a 15,000 lb. capacity.

138", 144", 150", 156" 156", 160", 168" 180"-192" 204"-218"





. Optional Wheel Lift 3,000 lb or 4,000 lb IRL Wheel Lift.

5. Optional Ladder Folding three-step ladder.



6. Optional Hydraulic Stabilizer with 4,000 lb Wheel Lift Includes No-Lube[™] pivot joints and 4-way receptacle for auxiliary tow lights and direct mount hydraulic counterbalance holding valves, if applicable.