

NOTES

маш
 WARD
VING FORWAR
MOVI
Monitov
Warnex
3000 South Austin Av
Georgetown, TX. USA
Telenhone 512-042-3
Facsimile 512-863-3
www.manitex.com

UPTime is the Manitex commitment to complete support of thousands of units working every day.



- and site visits.



venue 78626 3000 3776

MTX-TB-Guide-EN-V3-1117

<u>UPTime</u>

• Includes 24-7-365 parts assistance.

• Utilizes the efficiency of the Manitex Online Parts Search & Order System.

 Relies on Manitex's UPTrak support tracking system for performance analysis and resource allocation.

• Features REMan. Manitex's cost effective rebuild/exchange program.

• Provides expert service technicians for troubleshooting

• Mandates training; at our facility and yours. It includes coordinated support from all component suppliers.

 Involves every Manitex team member in the support of every Manitex customer.

What does UPTime mean to Manitex customers?

UPTime means reliability. **UPTime** means utilization. **UPTime** means profitability



features

- Single elevate cylinder design reduces weight and provides increased load clearance
- Proven pistol grip radio remote controls as standard
- Optional pneumatic control system availabe for dual control reliability
- Box-type boom constructed of high strength steel for increased strength to weight ratio
- Continuous boom rotation
- Low pressure, open centered hydraulic valves increase reliability and reduce hydraulic
- · Flow divider allows the JIFFY-LIFT[™] and SIDE-O-MATIC[™] to perform several functions simultaneously and efficiently
- Pilot-operated load holding valves on all cylinders
- Hydraulic outrigger options for increased stability
- Designed for truck or trailer installation
- Wide variety of factory approved forks and lifting devices available
- Optional bearing risers provide increased load clearance under boom

series 110 & PC **TROLLEY BOOMS**







series 110 & PC

BOOM

PC-20 C – 26' 1" overall length. 22' with hook out and 55" with hook in. Boom extension radius of 23' 11".

110-26 \mathbf{E} – 17' 2" overall retracted length. 25' 3" with hook out, and 14" with hook in. Boom extension radius of 26'.

110-35 E - 22' 3" overall retracted length. 34' 2" with hook out, and 14" with hook in. Boom extension radius of 35'.

HOIST

The lift cable arrangement resembles a block and tackle system operating in reverse. A lift cylinder pulls on the multiple sheave pack that carries the lift cable. The weaving design used throughout the boom maintains a constant hook height regardless of the amount of boom extension.

SWING SYSTEM

360° continuous rotation, equipped with a worm-type gear swing reducer driven by a roller vane-type hydraulic motor. Machines are calibrated to 1 rpm at max engine rpm.

OUTRIGGERS

Outriggers – Optional A-Frame or Out/ Down hydraulic outriggers for increased stability.

MOUNTING

Trailer or Truck Mounted – Trailer mounted unloaders utilize our "Classic" Pedestal/Base, and require only 24" (609 mm) of above deck load space. This "Classic" pedestal sits on top of the deck, and bolts to the trailers frame rails.

MECHANISMS

Trolley Systems – **PC** series fixed length boom offer smooth and fast trolley operation. Straight trolley boom design allows easy operation of all functions.

The **110-26 E & 110-35 E** three-section telescoping trolley booms are ideal for unloading with hook travel to within 14 inches of the pedestal without elevation.

CONTROL SYSTEM

A radio remote control system is standard. To promote optimum "Uptime" a dual control system can be achieved with the addition of the optional USTC SHOCKGUARD control system.

Unloader Safety Devices:

The hydraulic system incorporates such features as integral load holding valves for each cylinder, and system relief valving as standard.

The optional patented SHOCKGUARD Pneumatic Remote Control System, allows the operator to follow the load, while providing a measure of protection against electrical hazards. Troubleshooting and field service are simplified due to the elemental straight-forward design of the USTC SHOCKGUARD system.

ELECTRICAL SYSTEMS

Engine – Trailer mounted units can be self-powered or PTO powered, with a wetline kit. An 18 horsepower auxiliary gas engine is an option to PTO operation. All service parts are above the deck where they are easily accessed.

GENERAL

Service Network – Throughout North America our customers are supported by our extensive distributor sales and service network.

Options – Available options include a radio remote and a wide variety of hooks, pipe handling forks, highway barrier clamps, risers, power packs, anti-two blocking devices, auxiliary stabilizers, and more.

Warranty – 12 month warranty covers parts and labor resulting from defects in material workmanship.

* In order to ensure continuous improvement, specifications may change without notice.





CHASSIS DATA

Standard Specifications	PC-20 C
Maximum Lift Capacity at 11' (3,40 m)*	20,000 lb <i>(9 090 kg)</i>
Maximum Lift Capacity at 22' (6,71 m)*	10,000 lb (4 545 kg)
Cable Payout from Trolly	17' 6.5" <i>(5,40 m)</i>
Elevation	40°
Rotation	Continuous 1 rpm
Minimum Frame Required	3.2 rbm

* Less Attachment Weight

model 110-26 E 110-35 E

model PC-20 C



	PC-20 C
Pump Flow	12 gpm <i>(45 lpm)</i>
Recommended Truck Engine Speed	1,200 rpm
Operating Pressure	2,500 psi <i>(17,236 kPa)</i>



CHASSIS DATA	۱	
Standard Specifications	110-26 E	110-3
Maximum Lift Capacity at 18' (5,50 m)*	11,000 lb (4 989 kg)	11,000 <i>(4 989</i>
Maximum Lift Capacity at 25' (7,62 m)*	6,500 lb <i>(2 948 kg)</i>	-
Maximum Lift Capacity at 35' (10,70 m)*	-	4,000 (1 814
Minimum Radius Retracted	11' 6" <i>(3,51 m</i>)	15' 1 (4,60
Maximum Radius	43° (1,09 m)	43° (1,09
Cable Payout from Trolley	19' <i>(5,80 m)</i>	20' <i>(6,10</i>
Elevation	59°	59 °
Rotation	Continuous 1 rpm	Continu 1 rpr
Minimum Frame Required	2.5 rbm	2.5 rb
* Less Attachment Weight		

	WEIGHTS		
		110-26 E	110-35 E
	Basic Unit (classic includes outrigger weight)	5,900 lb (2 676 kg)	6,700 lb (3 039 kg)
	AS-6 A-Frame Outrigger	1,500 lb (680 kg)	1,500 lb (680 kg)
	HS-6 Drop Down Outrigger	630 lb (285 kg)	630 lb (285 kg)
	ER-20 Radial Out/Down Outrigger	1,370 lb (621 kg)	1,370 lb (621 kg)
	AS-6 Extra-Wide A-Frame Outrigger	2,020 lb <i>(916 kg)</i>	2,020 lb (916 kg)
1			

HYDRAULIC SYSTEM

		110-26 E	110-35 E
	Pump Flow	24 gpm <i>(90 lpm)</i>	12 gpm <i>(45 lpm)</i>
1	Recommended Truck Engine Speed	1,200 rpm	1,200 rpm
	Operating Pressure	2,400 psi (16,547 kPa)	2,400 psi <i>(16,547 kPa)</i>

OAH - Overall Height, BER - Boom Extension Radius, LC - Load Clearance, FSE - Front Stinger Extension, RSE - Rear Stinger Extension, BAT - Bed Assembly Thickness, CG - Center of Gravity from Center Line of Rotation