# AB80J/AB85J ARTICULATED BOOM LIFTS



- The ultimate diesel articulated booms
- Excellent aerial maneuverability with "up & over" capabilities
- Powerful 4 wheel drive and 4 wheel steer
- Smooth, precise, easy to use controls
- Simple to maintain and service



# ARTICULATED BOOM LIFTS

DIMENSIONS	AB80J	AB85J
Max. working height	85 ft 11 in	90 ft 6 in
Max. platform height	79 ft 11 in	84 ft 6 in
Max. horizontal reach	59 ft 5 in	61 ft 11 in
Clearance height at max. outreach	27 ft 11 in	27 ft 11 in
Platform size	8 ft x 3 ft	8 ft x 3 ft
Overall width ( <b>A</b> )	8 ft 6 in	8 ft 6 in
Overall length ( <b>B</b> )	32 ft 2 in	41 ft 2 in
Stowed height ( <b>C</b> )	9 ft 10 in	9 ft 10 in
Ground clearance	13 in	13 in

### PERFORMANCE

Platform capacity (SWL)	500 lbs	500 lbs
Max. wind speed	28 mph	28 mph
Max. drive height	79 ft 11 in	84 ft 6 in
Max. drive speed (stowed)	3.0 mph	3.0 mph
Max. drive speed (elevated)	0.6 mph	0.6 mph
Jib length	5 ft	6 ft 6 in
Jib arc	140°	135°
Jib rotation	n/a	140° side to side
Platform rotation	150°	150°
Superstructure rotation (continuou	s) 360°	360°
Tailswing	35 in	35 in
Raise/lower time	240/240 seconds	240/240 seconds
Gradeability	30%	30%
Inside turning radius	7 ft 10 in	7 ft 10 in
Outside turning radius	15 ft 5 in	15 ft 5 in
Tires	15 x 625 foam filled lug	
Controls	proportional joystick	
Drive system	4 wheel drive	

36,800 lbs

#### POWER

Power source


Kubota V2403 65hp diesel - Tier 4 Final

38,580 lbs


#### WEIGHT

Weight





**AB80J/AB85J** 



## **STANDARD FEATURES**

- Snorkel Guard<sup>™</sup> secondary guarding system •
- Hydraulic platform rotation
- Four wheel drive, steer and crab steer
- Foam filled lug tires •
- 360° continuous turntable rotation •
- Proportional drive, lift & swing, extend & rotate •
- Drive motion alarm •
- Flashing amber light •
- Horn •
- Dual lanyard attachment points
- Power line to platform •
- 5° tilt alarm •
- 2 year parts & labor, 5 year structural warranty
- ANSI compliant

# **OPTIONS**

- Special paint colors
- Airline to platform
- Non-marking tires
- AC generator 110V/240V 2kW
- Aircraft package
- Deluxe aircraft package •
- Cold weather package •
- Extreme cold weather package •
- Extreme environment package
- Light package
- Tow kit
- Glazier package
- Utility package
- 12kW generator package
- 12kW generator/welder package
- Dual fuel
- Environmental hydraulic oil
- Tool tray
- CSA compliant

www.snorkellifts.

P.O. Box 1160 St.Joseph, MO 64502-1160, USA Tel: 1 (785) 989-3000 Toll-free: 1 (800) 255-0317 Fax: 1 (785) 989-3070 Email: sales.usa@snorkellifts.com

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. ©Snorkel 2019 Refer to appropriate Snorkel operators manual for detailed instructions on the proper use and maintenance

:com