

How to Order GTS-XLS

Heavy-Duty Grade 1 Cylindrical Lock

QTY	SERIES	FAMILY	FUNCTION	TRIM	FINISH	HANDING	BACKSET	STRIKE	CYLINDER	KEYWAY	KEYING	OPTIONS
	GTS	XLS	116	PHL	626	RH	234	ASA	D	SCC	KD	—
				BSN	606	LH	234 - 2-3/4" (default)	ASA - ANSI/ASA (default) FL - Full Lip T - "T" Strike	D - Default L - Less Cylinder SF6 - SFIC w/ Core, 6 Pin SF7 - SFIC w/ Core, 7 Pin LF - Schlage® Compatible LFIC w/Core SFL - SFIC Housing less core LFL - Schlage® Compatible LFIC Housing less core55	AR1	KD - Keyed Different KO - Zero Bitted KA - Keyed Alike KE - Keyed to Existing MK - Master Key CMK - Construc- tion Master Key	TC10S - Tactile Abrasive Coating - Outside only TC2 - Tactile Abrasive Coating - Both Sides SF - Split Fin- ishes LL - Lead- Lined Rose DB - Dust Box AM - Antimicrobial Coating
			MIA	612		C059A1						
				613		C06						
				622		CL4						
										RUD		
										SCE		
										SCC		
										SCC-K		
										SAL		
										RA-RC		
										YA8		
										GA		
										FAL		
										KW		
										TA		
										A (Best Keyways)		
										PDQ1		
										PDQ2		
										PDQ3		



Headquarters: 2230 Embassy Drive, Lancaster, PA 17603
 Phone: 866.874.3662 | Email: smartsupport@pdqlocks.com
www.pdqsmartnetworked.com