

10-HP Hydraulic Unit

ADVANTAGES

- Pendant operated for safe and convenient operation
- Heavy cuts, high metal removal rates
- Will operate a variety of York's tools
- Reversible hydraulic drive
- Available in several voltages
- Proportional rotation

APPLICATIONS

- Logging
- Mining
- Construction
- Marine
- Crushers
- Excavators stick, boom mount, lift cylinder mount

PRODUCT DESCRIPTION

The 10-hp hydraulic power unit is conveniently and safely controlled by a remote pendant providing increased machining rates over longer periods of time. This allows for easy, heavy cuts with higher metal removal rates. Remote operations with the pendant include e-stop, forward, reverse, rapid feed, and bar drive on/off. The 10-hp power unit is designed for use with 4-14HD, 12-36, ILT-1000, ILT-1600, LMM-72 and RMM-66.



- Gears and gear boxes
- Loaders, buckets
- Motor housings and shafts
- Pumps
- Turbines
- Custom designed applications



General Information		
Flow	10.5 gpm (40 lpm) @ 1600 psi	
Tank	15 gal (53 L) - uses AW 46 Oil	
Weight	455 lbs dry (206.4 kg)	

Electric Motor Voltage and Current Chart					
10 HP Three-Phase Electric Reversible Hydraulic Drive					
Full Load Ratings					
VOLTS	AMPS	HZ			
230	23.6	50			
230	23.6	60			
380	13.8	50			
400	13.8	50			
415	11.8	50			
460	11.8	50			
460	11.8	60			
575	9.5	60			

Maximum Continuous Value at Boring Bar				
RPM MAX	RPM MIN	TORQUE FT-LB (NM)	DISPLACEMENT IN3 (CC)	
90	20	333 (449)	22.6 (370)	
150	30	208 (280)	14.1 (230)	
280	60	106 (141)	7.3 (120)	
460	90	65 (87)	3.6 (59)	

*specifications limited by boring bar motor







sales@sprentalsllc.com

sprentalsllc.com